



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 24-8170-3 | Version Number: | 7.00 |
| Issue Date: | 05/22/18 | Supersedes Date: | 10/13/17 |

SECTION 1: Identification

1.1. Product identifier

3M™ Dynatron® Liquid Hardener 609

Product Identification Numbers

60-4550-5422-5, 70-0080-0385-0

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Automotive Aftermarket |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Organic Peroxide: Type D.
Acute Toxicity (oral): Category 4.
Acute Toxicity (inhalation): Category 4.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 1C.
Reproductive Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark |

Pictograms**Hazard Statements**

Heating may cause a fire.

Harmful if swallowed.

Causes severe skin burns and eye damage.

Harmful if inhaled.

Suspected of damaging fertility or the unborn child.

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep away from clothing and other combustible materials.

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Protect from sunlight.

Store at temperatures not exceeding 5C/40F. Keep cool.

Store locked up.

Store away from other materials.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

Supplemental Information:

May cause thermal burns.

25% of the mixture consists of ingredients of unknown acute oral toxicity.

50% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---------------|------------------------|
| Dimethyl Phthalate | 131-11-3 | 30 - 50 Trade Secret * |
| Methyl Ethyl Ketone Peroxide | 1338-23-4 | 20 - 40 Trade Secret * |
| Phlegmatizer | Trade Secret* | 10 - 30 Trade Secret * |
| Methyl Ethyl Ketone | 78-93-3 | 0 - 10 Trade Secret * |
| Water | 7732-18-5 | 0 - 5 Trade Secret * |
| Hydrogen Peroxide | 7722-84-1 | < 3 Trade Secret * |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | 92257-31-3 | 0.1 - 1 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|-------------------------------|-------------------|
| Acetic Acid | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Ketones | During Combustion |
| Toxic Vapor, Gas, Particulate | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin contact with hot material. Avoid breathing of dust created by cutting, sanding, grinding or machining. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store at temperatures not exceeding 25C/77F. Keep cool. Keep only in original container. Store away from acids. Store away from oxidizing agents. Store away from other materials. Keep/store away from clothing and other combustible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------------------------|------------|--------|-------------------------------------|------------------------------|
| Dimethyl Phthalate | 131-11-3 | ACGIH | TWA:5 mg/m ³ | |
| Dimethyl Phthalate | 131-11-3 | OSHA | TWA:5 mg/m ³ | |
| Methyl Ethyl Ketone Peroxide | 1338-23-4 | ACGIH | CEIL:0.2 ppm | |
| Hydrogen Peroxide | 7722-84-1 | ACGIH | TWA:1 ppm | A3: Confirmed animal carcin. |
| Hydrogen Peroxide | 7722-84-1 | OSHA | TWA:1.4 mg/m ³ (1 ppm) | |
| Methyl Ethyl Ketone | 78-93-3 | ACGIH | TWA:200 ppm;STEL:300 ppm | |
| Methyl Ethyl Ketone | 78-93-3 | OSHA | TWA:590 mg/m ³ (200 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber
Boots - Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following

respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| General Physical Form: | Liquid |
| Odor, Color, Grade: | Red liquid with faint ketone odor. |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>No Data Available</i> |
| Melting point | <i>No Data Available</i> |
| Boiling Point | <i>No Data Available</i> |
| Flash Point | ≥200 °F [<i>Test Method</i> :Closed Cup] |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | <i>No Data Available</i> |
| Flammable Limits(UEL) | <i>No Data Available</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 1.1 g/ml |
| Specific Gravity | 1.1 [<i>Ref Std</i> :WATER=1] |
| Solubility In Water | <i>No Data Available</i> |
| Solubility in Water | Slight (less than 10%) |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | <i>No Data Available</i> |
| Hazardous Air Pollutants | 43.1 % weight [<i>Test Method</i> :Calculated] |
| Volatile Organic Compounds | 63 g/l [<i>Test Method</i> :Tested per ASTM protocol] |
| Volatile Organic Compounds | 5.7 % weight [<i>Test Method</i> :Tested per ASTM protocol] |
| VOC Less H2O & Exempt Solvents | 64 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Unstable. This product should be stored at temperatures below 80 F (27 C).

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids
Strong oxidizing agents
Alkali and alkaline earth metals
Reducing agents
Accelerators

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

During heating:

Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

During heating:

Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or coloration.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|--------------------------------|---------|--|
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE10 - 20 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE300 - 2,000 mg/kg |
| Dimethyl Phthalate | Inhalation-Dust/Mist (4 hours) | Other | LC50 > 15.1 mg/l |
| Dimethyl Phthalate | Dermal | Rabbit | LD50 > 11,940 mg/kg |
| Dimethyl Phthalate | Ingestion | Rat | LD50 6,800 mg/kg |
| Methyl Ethyl Ketone Peroxide | Dermal | Rabbit | LD50 4,000 mg/kg |
| Methyl Ethyl Ketone Peroxide | Inhalation-Vapor (4 hours) | Rat | LC50 15.4 mg/l |
| Methyl Ethyl Ketone Peroxide | Ingestion | Rat | LD50 484 mg/kg |
| Methyl Ethyl Ketone | Dermal | Rabbit | LD50 > 8,050 mg/kg |
| Methyl Ethyl Ketone | Inhalation-Vapor (4 hours) | Rat | LC50 34.5 mg/l |
| Methyl Ethyl Ketone | Ingestion | Rat | LD50 2,737 mg/kg |
| Hydrogen Peroxide | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Hydrogen Peroxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 2 mg/l |
| Hydrogen Peroxide | Ingestion | Rat | LD50 1,193 mg/kg |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------------------|---------|--------------------|
| Methyl Ethyl Ketone Peroxide | Rabbit | Corrosive |
| Methyl Ethyl Ketone | Rabbit | Minimal irritation |
| Hydrogen Peroxide | Rabbit | Corrosive |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| Methyl Ethyl Ketone Peroxide | Human | Corrosive |
| Methyl Ethyl Ketone | Rabbit | Severe irritant |
| Hydrogen Peroxide | Rabbit | Corrosive |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|------------------------------|------------|----------------|
| Methyl Ethyl Ketone Peroxide | Human | Not classified |
| Hydrogen Peroxide | Guinea pig | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| Methyl Ethyl Ketone Peroxide | In vivo | Not mutagenic |
| Methyl Ethyl Ketone Peroxide | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Methyl Ethyl Ketone | In Vitro | Not mutagenic |
| Hydrogen Peroxide | In vivo | Not mutagenic |
| Hydrogen Peroxide | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | In vivo | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|------------------------------|---------------|-------------------------|--|
| Methyl Ethyl Ketone Peroxide | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Methyl Ethyl Ketone | Inhalation | Human | Not carcinogenic |
| Hydrogen Peroxide | Dermal | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Hydrogen Peroxide | Ingestion | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|---------------|--|---------|---------------------|--------------------------------|
| Methyl Ethyl Ketone Peroxide | Dermal | Not classified for female reproduction | Rat | NOAEL 70 mg/kg/day | 13 weeks |
| Methyl Ethyl Ketone Peroxide | Ingestion | Not classified for female reproduction | Rat | NOAEL 75 mg/kg/day | prematuring & during gestation |
| Methyl Ethyl Ketone Peroxide | Ingestion | Not classified for male reproduction | Rat | NOAEL 75 mg/kg/day | 28 days |
| Methyl Ethyl Ketone Peroxide | Dermal | Not classified for male reproduction | Rat | NOAEL 70 mg/kg/day | 13 weeks |
| Methyl Ethyl Ketone Peroxide | Ingestion | Not classified for development | Rat | NOAEL 50 mg/kg/day | prematuring & during gestation |
| Methyl Ethyl Ketone | Inhalation | Not classified for development | Rat | LOAEL 8.8 mg/l | during gestation |
| Hydrogen Peroxide | Ingestion | Not classified for female reproduction | Rat | LOAEL 5 mg/kg/day | 6 months |
| Hydrogen Peroxide | Ingestion | Not classified for male reproduction | Rat | LOAEL 5 mg/kg/day | 6 months |
| Hydrogen Peroxide | Ingestion | Not classified for development | Rat | LOAEL 5 mg/kg/day | during gestation |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | Not Specified | Not classified for development | Rat | NOAEL Not available | prematuring & during gestation |
| 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. | Not Specified | Toxic to female reproduction | Rat | LOAEL 20 mg/kg/day | prematuring & during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------------|------------|-----------------------------------|--|-------------------------|---------------------|------------------------|
| Methyl Ethyl Ketone Peroxide | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Methyl Ethyl Ketone | Inhalation | central nervous system depression | May cause drowsiness or dizziness | official classification | NOAEL Not available | |
| Methyl Ethyl Ketone | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Methyl Ethyl Ketone | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| Methyl Ethyl Ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | not applicable |
| Methyl Ethyl Ketone | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 1,080 mg/kg | not applicable |
| Hydrogen Peroxide | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | |
| Hydrogen Peroxide | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Human | LOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------------|------------|--|----------------|------------|----------------------|-------------------|
| Methyl Ethyl Ketone Peroxide | Dermal | heart hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 70 mg/kg/day | 13 weeks |
| Methyl Ethyl Ketone Peroxide | Ingestion | liver kidney and/or bladder | Not classified | Rat | LOAEL 97 mg/kg/day | 7 weeks |
| Methyl Ethyl Ketone | Dermal | nervous system | Not classified | Guinea pig | NOAEL Not available | 31 weeks |
| Methyl Ethyl Ketone | Inhalation | liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles | Not classified | Rat | NOAEL 14.7 mg/l | 90 days |
| Methyl Ethyl Ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | 7 days |
| Methyl Ethyl Ketone | Ingestion | nervous system | Not classified | Rat | NOAEL 173 mg/kg/day | 90 days |
| Hydrogen Peroxide | Ingestion | hematopoietic system | Not classified | Rat | NOEL 0.005 mg/kg/day | 6 months |
| Hydrogen Peroxide | Ingestion | liver kidney and/or bladder | Not classified | Mouse | NOAEL Not available | 35 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Organic peroxide

Health Hazards

Acute toxicity

Hazard Not Otherwise Classified (HNOC)

Reproductive toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|--------------------|------------------|----------------------|
| Dimethyl Phthalate | 131-11-3 | Trade Secret 30 - 50 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 2 **Instability:** 2 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 3 **Flammability:** 2 **Physical Hazard:** 2 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 24-8170-3 | Version Number: | 7.00 |
| Issue Date: | 05/22/18 | Supersedes Date: | 10/13/17 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com