



CRC Industries NZ, Auckland NZ

I. Product Description

CRC Aeroclean Degreaser delivers a concentrated jet of cleaning solution that dissolves and removes oil and grease from dirty engines. It leaves a detergent on the surface which emulsifies the remaining contaminants when flushed with water.

CRC AeroClean Degreaser restores and improves the appearance of your engine. It is a unique combination of non-corrosive surfactants, detergents and solvents, so it can also be used safely to clean concrete floors and driveways.

It is excellent on all automotive engines and mechanical equipment that is contaminated with grease, oil and grime.

II. Features & Benefits

- Highly concentrated jet to penetrate the grease and grime build-up
- Easy & Convenient - Water wash-off with no residue
- Restores & enhances the appearance of your engine
- A unique combination of surfactants, detergents and solvents
- Non-corrosive
- Cleans concrete floors and driveways
- MPI Approved C12

III. Application and Directions

Preparation:

- Before cleaning a motor, run for a short period of time to warm it as this assists drying off.
- Shake can well before use.

Application:

- Spray on greasy or oily surfaces and allow to penetrate for 5-10 minutes.
- Do not spray directly onto hot exhaust manifolds.
- Hose off with pressure.
- Heavy or thick deposits may have to be loosened with a scraper or brush. If necessary, spray area again and hose off with pressure.
- Should you experience difficulty in starting your motor, use CRC 5.56 to displace moisture in the distributor and electrics.
- Do not use on plastic engine covers.
- Do not allow product to come in contact with bitumen surfaces.

IV. Typical Properties and Characteristics

Physical Properties:

<i>Flash Point</i>	40 °C
<i>Vapour Pressure</i>	60 psig @ 20°C
<i>Specific Gravity</i>	0.850

V. Package Description

Part Number	Size
5070	500ml Aerosol



CRC Industries NZ, Auckland NZ

VI. Special Precautions**General:**

Highly flammable liquid and vapour. Extremely flammable aerosol. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. Store in a well-ventilated place. Store locked up. Keep cool. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Do not induce vomiting. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol.

Skin – Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.

Eyes – Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention.

Inhalation – Remove from contaminated area. Lay patient down. Keep warm and rested.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 08/2015

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.