



1. The top plate is the main component of the assembly. It is made of a material that is resistant to corrosion and has a high strength-to-weight ratio. It is designed to provide a stable base for the other components.

2. The central shaft is a critical component that connects the top plate to the bottom plate. It is made of a material that is strong and durable, and it is designed to withstand the forces applied to the assembly.

3. The middle ring is a component that provides additional support and stability to the assembly. It is made of a material that is resistant to wear and tear, and it is designed to fit snugly around the central shaft.

4. The bottom plate is the base of the assembly. It is made of a material that is resistant to corrosion and has a high strength-to-weight ratio. It is designed to provide a stable base for the other components.

5. The top plate is attached to the central shaft using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the top plate and the central shaft.

6. The middle ring is attached to the central shaft using a pin. The pin is made of a material that is strong and durable, and it is designed to provide a secure connection between the middle ring and the central shaft.

7. The bottom plate is attached to the central shaft using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the bottom plate and the central shaft.

8. The top plate is attached to the middle ring using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the top plate and the middle ring.

9. The middle ring is attached to the bottom plate using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the middle ring and the bottom plate.

10. The central shaft is attached to the bottom plate using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the central shaft and the bottom plate.

FALCETILE



1. The top plate is the main component of the assembly. It is made of a material that is resistant to corrosion and has a high strength-to-weight ratio. It is designed to provide a stable base for the other components.

2. The central shaft is a critical component that connects the top plate to the bottom plate. It is made of a material that is strong and durable, and it is designed to withstand the forces applied to the assembly.

3. The middle ring is a component that provides additional support and stability to the assembly. It is made of a material that is resistant to wear and tear, and it is designed to fit snugly around the central shaft.

4. The bottom plate is the base of the assembly. It is made of a material that is resistant to corrosion and has a high strength-to-weight ratio. It is designed to provide a stable base for the other components.

5. The top plate is attached to the central shaft using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the top plate and the central shaft.

6. The middle ring is attached to the central shaft using a pin. The pin is made of a material that is strong and durable, and it is designed to provide a secure connection between the middle ring and the central shaft.

7. The bottom plate is attached to the central shaft using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the bottom plate and the central shaft.

8. The top plate is attached to the middle ring using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the top plate and the middle ring.

9. The middle ring is attached to the bottom plate using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the middle ring and the bottom plate.

10. The central shaft is attached to the bottom plate using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the central shaft and the bottom plate.

11. The top plate is attached to the middle ring using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the top plate and the middle ring.

12. The middle ring is attached to the bottom plate using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the middle ring and the bottom plate.

13. The central shaft is attached to the bottom plate using a screw. The screw is made of a material that is strong and durable, and it is designed to provide a secure connection between the central shaft and the bottom plate.