



CRC Industries NZ
Auckland NZ

I. Product Description

CRC Strip Off Paint Stripper is a fast aerosol stripper which removes paint and varnish from most types of surfaces including paint brushes. The convenient aerosol can easily sprays hard-to-reach areas and will not drip or run.

It can also be used for removing fat and loose surface rust from BBQ plates, gaskets from motors, pumps and machinery plus decarbonising lawn mowers, marine outboard motors and motor cycles. CRC Strip Off Paint Stripper also removes graffiti.

II. Features & Benefits

- Ease of use saves time
- No mess aerosol applications for improved user safety
- Saves on brushes and containers
- No wastage due to accurate spray
- Thickness of Gel Coat can be managed easily
- Doesn't drip or run
- Easy clean up
- Spray gets into hard to reach areas

III. Application and Directions

1. Shake can vigorously before and during application. Protect areas that do not require stripping.
2. Spray in smooth even coats rather than a heavy coat and leave 5-10 minutes for the paint to bubble and blister.
3. Remove with a metal scraper, spatula or wash off. Allow to dry thoroughly.
4. A second application may be necessary depending on the type, thickness and age of coating.
5. All surfaces should be washed thoroughly with clean water prior to repainting or varnishing. Light sanding may be required on some surfaces.
6. Timber surfaces should be lightly sanded before repainting or varnishing.

Note: CRC Strip Off should not be used on fiberglass, plastics, styrene related plastics, vinyl, laminex or laminated surfaces. If used to remove graffiti on painted surfaces, CRC Strip Off may also strip the base colour.

IV. Typical Properties and Characteristics

Physical Properties:

Appearance	White gel
Flash Point	-81 °C (Propellant)
Propellant	Hydrocarbon
Flammability	Non-flammable aerosol

Performance Characteristics:

Theoretical coverage	2m ²
Stripping Time	5-30 minutes



CRC Industries NZ
Auckland NZ

V. *Package Description*

Part Number	Size
5115	500ml Aerosol

VI. *Special Precautions*

General:

Extremely flammable aerosol. Keep away from naked flames, electrical appliances/lights, lighted cigarettes, etc. Use with adequate ventilation. Store in a cool, well-ventilated area. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50 °C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Avoid giving milk, oils or alcohol. Not considered a normal route of entry.

Skin – Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents.

Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay.

Inhaled – Remove to fresh air. Lay patient down. Keep warm and rested.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 02/2012

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.