

POLYETHYLENE MASKING TAPE FOR STUCCO APPLICATION



DESCRIPTION

This tape has a durable, moisture resistant LDPE (polyethylene) backing with a rubber-based pressure-sensitive adhesive. It bonds well to a variety of surfaces and removes cleanly.

MAIN FEATURES

- Designed to offer a high degree of conformability without excessive stretch.
- Stiffer backing makes it easier to handle in certain applications.
- UV resistance up to 90 days, depending upon conditions and surfaces.
- Removes cleanly from most opaque surfaces up to 90 days.
- Easy to unwind.

APPLICATIONS

- Masking against overspray when applying stucco and EIFS.
- Protecting surfaces such as windows, doors and frames,
- Seaming and sealing polysheeting and film indoors and outdoors where UV exposure is prevalent.

SPECIFICATION CONFORMANCE

- Tested in accordance with UL723 / ASTM E84.

TECHNICAL DATA

Colour	Red
Backing	Polyethylene (PE) Film
Adhesive.....	Synthetic Rubber
Adhesion to steel.....	75 oz/in (21 N/25mm)
Tensile strength	21 lbs/in (92 N/25mm)
Elongation	75% at break
Thickness.....	7.0 mil
Temperature Resistance	176°F (80°C) for 30 minutes
Application Temperature Range	+45°F ~ +120°F (+7°C ~ +49°C)
Operating Temperature Range	+20°F to +200°F (-7°C to +93°C)

UV RESISTANT

HIGH HOLDING POWER

**NOW
90 DAY
CLEAN REMOVAL**

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice obligation in our products and publications.