


SUBMERSIBLE PUMP CABLE



APPLICATIONS Suitable for use as follows:

- For use with submersible pumps and irrigation equipment
- For wiring only between equipment located at water wellheads and motors of submersible pumps installed in deep wells

STANDARDS & REFERENCES

- CSA Spec. C22.2. No. 75; CSA LL90458
- UL Spec. No. 493
- TWU/UF CSA LL90458; ULE30445

CONSTRUCTION

- Solid or stranded bare copper conductors
- Individual PVC insulation
- Twisted without fillers

**Solid or Stranded Bare
Copper Conductors**

**Individuals
PVC Insulation**

**3 or 4 Twisted
Conductors**

**600 Volts,
Maximum 60°C**

**Sunlight &
Weather Resistant**



SPECIALTY CORD

SUBMERSIBLE PUMP CABLE

WEIGHTS, MEASUREMENTS AND PACKAGING

SIZE AWG	NO. OF COND.*	COND. STRD.	MIN. GROUND WIRE AWG	INSULATION THICKNESS		NOMINAL OVERALL DIAMETER		AMPS	NET WEIGHT	
				mm	inches	mm	inches		kg/km	lbs/Mft
14	3	1	14	1.52	.06	10.1	.398	15	116.05	77.99
12	3	1	12	1.52	.06	11.02	.434	20	157.14	105.61
14	3	7	14	1.52	.06	10.57	.416	15	123.34	82.89
12	3	7	-	1.52	.06	11.61	.457	20	167.35	112.47
12	3	7	8	1.52	.06	13.61	.536	20	239.36	160.86
10	3	7	10	1.52	.06	13.26	.522	30	232.02	155.93
14	4	1	14	1.52	.06	11.29	.444	15	154.73	103.98
12	4	1	12	1.52	.06	12.31	.485	20	209.52	140.81
10	4	1	10	1.52	.06	13.61	.536	30	293.21	197.05
14	4	7	14	1.52	.06	11.82	.465	15	164.45	110.52
12	4	7	12	1.52	.06	12.97	.511	20	223.14	149.96
12	4	7	8	1.52	.06	12.97	.511	20	295.14	198.35
10	4	7	10	1.52	.06	14.29	.562	30	309.36	207.9
8	4	7	10	2.03	.08	18.74	.738	40	460.7	309.61
6	4	7	8	2.03	.08	21.07	.83	55	675.85	454.2

* Number of Conductors includes green ground wire.