

SAFETY DATA SHEET

1. Identification

Product identifier Hi Temperature Disc Brake Wheel Bearing Grease - 35 lbs

Other means of identification

Product Code No. SL3165 (Item# 1007882)

Recommended use Wheel bearing grease

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2

Sensitization, skin Category 1
Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements

Environmental hazards



Signal word Warning

Hazard statement May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long

lasting effects.

Precautionary statement

Prevention Avoid breathing vapors. Wash thoroughly after handling. Contaminated work clothing must not be

allowed out of the workplace. Wear protective gloves. Wear eye/face protection. Avoid release to

the environment.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: Hi Temperature Disc Brake Wheel Bearing Grease - 35 lbs No. SL3165 (Item# 1007882) Version #: 01 Issue date: 12-18-2019

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	15 - 40
tris(dipentyldithiocarbamato-s,s')ar imony	nt	15890-25-2	1 - 5
benzoic acid		65-85-0	0.5 - 1.5
calcium bis(dinonylnaphthalenesulphonate)	57855-77-3	0.5 - 1.5
distillates (petroleum), hydrotreate light naphthenic	d	64742-53-6	0.5 - 1.5
graphite		7782-42-5	0.1 - 1.5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Provide oxygen or artificial respiration if needed. Call a physician if symptoms

develop or persist.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes. In case of eczema or other skin disorders: Seek medical attention and take along

these instructions. Wash contaminated clothing before reuse.

Eye contact Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having Ingestion

convulsions. Do not induce vomiting without advice from poison control center. Get medical

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

vision. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Sweep up and shovel into suitable containers for disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

When using do not eat or drink. Wash contaminated clothing before reuse. Provide adequate ventilation. Avoid breathing vapors. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Keep away from heat and sources of ignition. Store away from incompatible materials (see Section 10 of the SDS). Keep container tightly closed.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Cont		Value	Form
Components	Туре	Value	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
tris(dipentyldithiocarbamato -s,s')antimony (CAS 15890-25-2)	PEL	0.5 mg/m3	
white mineral oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
US. OSHA Table Z-3 (29 CFR 1910.1000			
Components	Туре	Value	
graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limit Values Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.

Components	Туре	Value	Form
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
tris(dipentyldithiocarbamato -s,s')antimony (CAS 15890-25-2)	TWA	0.5 mg/m3	
white mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
tris(dipentyldithiocarbamato -s,s')antimony (CAS 15890-25-2)	TWA	0.5 mg/m3	
white mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
ogical limit values	No biological exposure limits noted f	41 :	

Biol

App controls

should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Latex. Rubber. **Hand protection**

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary. General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormGrease.ColorBlack.

Odor Mild petroleum.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

450 °F (232.2 °C) estimated

Flash point 475 °F (246.1 °C) Cleveland Open Cup

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressure Not available.
Vapor density Not available.

Relative density 0.9

Solubility(ies)

Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available.

Viscosity > 21 mm²/s (104 °F (40 °C))

Percent volatile Not available.

Other information

VOC 4.3 % estimated

4.3 % Switzerland estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Carbon oxides. N

products

Carbon oxides. Nitrogen oxides (NOx). Sulfur oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Can cause stomach ache and vomiting.

Symptoms related to the physical, chemical and toxicological characteristics Prolonged or excessive inhalation may cause respiratory tract irritation. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction. Expected to be a low hazard for usual industrial or

commercial handling by trained personnel.

Test Results Product Species

Hi Temperature Disc Brake Wheel Bearing Grease - 35 lbs

Acute Dermal

LD50 Rabbit 2592 mg/kg

Inhalation

LC50 Rat 100 mg/l, 4 hours

Oral

LD50 Rat 5305 mg/kg Components Species **Test Results**

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 2180 mg/m3, 4 hours

Oral

LD50 Rat > 5000 mg/kg

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

Acute

Dermal

LD50 Rabbit > 16000 mg/kg

Oral

LD50 Rat > 16400 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Based on available data, the classification criteria are not met.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

benzoic acid (CAS 65-85-0)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 180 mg/l, 96 hours

graphite (CAS 7782-42-5)

Aquatic Acute

Fish LC50 Fish > 1800 mg/l, 96 hours

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

Aquatic

Chronic

Crustacea NOEC Water flea (Daphnia magna) 0.02 mg/l, 21 days

Persistence and degradability

Not readily biodegradable.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

benzoic acid 1.87

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Material name: Hi Temperature Disc Brake Wheel Bearing Grease - 35 lbs No. SL3165 (Item# 1007882) Version #: 01 Issue date: 12-18-2019

^{*} Estimates for product may be based on additional component data not shown.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

benzoic acid (CAS 65-85-0)

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

CERCLA Hazardous Substances: Reportable quantity

benzoic acid (CAS 65-85-0)

5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Serious eye damage or eye irritation categories Respiratory or skin sensitization

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
tris(dipentyldithiocarbamato-s,s')antimony	15890-25-2	1 - 5	

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

benzoic acid (CAS 65-85-0)

graphite (CAS 7782-42-5)

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

US. Massachusetts RTK - Substance List

benzoic acid (CAS 65-85-0)

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

graphite (CAS 7782-42-5)

US. Pennsylvania Worker and Community Right-to-Know Law

benzoic acid (CAS 65-85-0)

graphite (CAS 7782-42-5)

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

US. Rhode Island RTK

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

graphite (CAS 7782-42-5)

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

tris(dipentyldithiocarbamato-s,s')antimony (CAS 15890-25-2)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR Not determined

51.100(s))

Consumer products N

(40 CFR 59, Subpt. C)

Not regulated

Inventory name

State

Consumer products Not regulated

VOC content (CA) 0.4 % VOC content (OTC) 0.4 %

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Chemical Substance Inventory (TCSI)
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 12-18-2019
Prepared by Dustin Kern

Version # 01

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

On inventory (yes/no)*

Yes

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).