



By properly utilizing a top scrub and recoat routine, stripping frequency can be greatly reduced, a more uniform level of appearance can be maintained, and overall floor care costs can be dramatically lowered. A deep scrub removes soil in the top layer of the floor finish and prevents dirt from being trapped between recoats. This process removes 1 - 1.5 layers of finish.



### People

- Team Assignments – 1 to 2 people. Who will be operating floor machine, applying scrubbing solution, running wet vacuum, etc.?
- Safety Equipment – wet floor signs, please refer to product Safety Data Sheets.



### Product & Equipment

- Dust mop
- Wet Floor signs
- Trident FMD20 - 175 rpm floor machine with pad holder or Trident FMD20 Orbital
- Trident Wet vacuum
- Blue or green scrub pad; or Trident Multi-Finish Prep Pad (MFPP)
- 3M Doodle Bug with Blue Scrub Pad
- 2 mop buckets with wringers
- 2 clean cotton or rayon mops with handles
- Hillyard Assurance® or Arsenal® Recoat Prep.





Procedures

1. Dust mop all flooring.
2. Set out Wet Floor signs.
3. Following label directions mix cleaner in mop bucket. (Assurance 6 oz. / gallon)
4. Apply a generous amount of the cleaner solution to approximately a 10 ft. by 20 ft. area. Allow the cleaning solution to dwell for 2 to 3 minutes
5. Scrub floor with a blue or green scrub pad or Trident Multi-Finish Prep Pad (MFPP). (note: if using an MFPP, flip the pad after 1000 sq. ft. of usage, and discard for a new pad after both sides of have used to scrub.)
6. Use Doodle bug scrub pad to detail scrub corners and floor to wall junction.
7. Pick up the scrub solution with a wet vacuum.
8. Damp mop rinse the floor with clean water. Change the rinse water as soon as it becomes cloudy. (note: in place of mopping, and auto-scrubber can be used to rinse the floor)
9. Continue with each section until all assigned flooring is scrubbed and rinsed.
10. Clean equipment and store properly, allow flooring to dry 30 minutes before applying finish.

