## INSTALLATION INSTRUCTIONS

Please read carefully and save these instruc ons as you may need them a later date.

## CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

## GENERAL

All electrical connec ons must be in accordance with local and Na onal Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connec ons obtain the services of a qualified electrician.

Remove the fixture and the moun ng package from the box and make sure that no parts are missing by referencing the illustra on.

## **ASSEMBLY AND INSTALLATION**

- 1. Pass the power cords through the stems (3) and the canopy (6), then thread the stems (3) onto glass shade (2) and thread the swivel (4) onto the top stem (3). Adjust the height of the fixture by either increasing or decreasing the stems (3).
- 2. Thread the socket assembly (1) onto the glass shade (2).
- 3. Attach the mounting bar (8) with box screws (7) to the outlet box.
- 4. Pull out the outlet wire and ground wire from the outlet box.
- Make wire connections with wire nut (9).
- --Connect the white wire (Neutral wire) from the light to the white wire from power source.
- --Connect the black wire (Live wire) from the light to the black wire from power source.
- --Wrap the grounding wire (green wire or bare copper wire) from the light around the green screw on the mounting bar (8), then connect it to the grounding conductor from power source.
- 5. At tach the fixture canopy (6) to the outlet box, secure it with the ball nuts (5).
- 6. Install one Type A 60W Max bulb (bulbs not included).
- (Don't exceed the maximum capacity recommended on the sockets).

