

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings LCP, LC6, L7X, L7XP, L7XPR and L7XR.

CONSTRUCTION

Aluminum white reflector.

Polyester powder coat paint.

White finish has integral flange.

INSTALLATION

Socket to trim interface.

Retaining clips riveted to top of reflector hold trim inside housing.

LISTINGS

UL Listed to US and Canadian safety standards.

Wet location listed.

WARRANTY

1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Catalog Number
Notes
Type

6" Finishing Trim

CL1/2

POLYCARBONATE LENS

Narrow Flange



Flush opal lens


Specifications

Height: 4 (10.2)

Lamp opening: 5-5/8 (14.3)

Diameter: 7-5/8 (19.4)

All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: CLF1

Series	Options
CLF1 Flush opal lens	PF Integral white plastic flange ¹

Housing Compatibility: Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	40 A19	LCP, LC6, L7X, L7XR
	Fluorescent	13DTT	L7XF

Notes

1 Flush lens (CLF1) with plastic flange option is not compatible with CFL housings.