

Nuvo® P500 Player Portfolio Sound Bar and Subwoofer

Home audio has never sounded so good. The Player Portfolio Sound Bar (NV-P500-XX) provides excellent sound quality through a powerful 2.1 system, complete with an eight inch wireless subwoofer. The Sound Bar can play audio from a video source such as a TV or can be used within the Player Portfolio system to access a variety of streaming services as well as any networked audio content.



- Excellent sound quality through a powerful 2.1 system, complete with an eight inch wireless subwoofer
- Play audio from a video source, such as TV or DVD player
- Use as a Player zone giving you access to networked audio content and streaming services like Spotify, Pandora, iHeartRadio, and more
- Sleek design with metal grill and capacitive touch backlit control
- Easily controlled with the included IR remote, Nuvo PoE Keypads, or with the Nuvo Player app
- TOSLINK and analog line input
- Third-party integration with control partners such as Crestron, Control4, KNX, RTI, URC, and more
- Ethernet or Wireless 802.11 a,b,g,n, 2.4GHz or 5GHz

*Streaming services subject to geographic availability. Service subscriptions may be required.

Nuvo® P500 Player Portfolio

Sound Bar and Subwoofer

Input/Output Connectors

Line Input	RCA / TOSLINK
USB Connection	One
Local Area Network (LAN)	RJ45, Cat5 minimum, 10/100baseT minimum

Supported Audio Formats

Music File (USB or over network)	MP3
	WMA
	AAC
	Ogg Vorbis
	FLAC
	WAV

Internet Radio:	Pandora
	Sirius/XM
	iHeart Radio
	TuneIn
	Spotify

IP Control

Apple iTouch®
Apple iPhone®
Apple iPad®
Android Mobile
Android Tablet

Network Connectivity

LAN (Wired Connection)	Ethernet,
	Wireless: 802.11 a,b,g,n 2.4 GHz or 5GHz band

Output

Distortion	0.5% max
Frequency Response	50Hz - 20KHz

Line Input:

Input Impedance	10K Ohms
Input Overload	2.2 V RMS

Regulatory Approvals

Safety	cTUVus, CE-LVD
EMC	US:FCC CFR Title 47 Part 15, Subpart B; CANADA:ICES-003; EUROPE:CISPR13; EUROPE: 55020; AUSTRALIA/NEW ZEALAND: C-TICK standard AS/NZS CISPR13
Environmental Compliance	RoHS

SPECIFICATIONS

Power Requirements

Input Voltage	110 – 240VAC, 50/60 Hz
Power Consumption (max)	120 W Soundbar; 80W Subwoofer
(typical - music)	75 W Soundbar; 50W Subwoofer

Operating Temperature

0° C to 40° C

Physical Specifications

Soundbar Size without feet (mm)	108 H x 877 W x 115 D
Soundbar Size without feet (inch)	4.25 H x 34.5 W x 4.5 D
Subwoofer Size without feet (mm)	235 H x 231 W x 303 D
Subwoofer Size without feet (inch)	9.25 H x 9.1 W x 11.9 D

Soundbar Size with feet (mm)	115 H x 877 W x 115 D
Soundbar Size with feet (inch)	4.5 H x 34.5 W x 4.5 D
Subwoofer Size with feet (mm)	261 H x 231 W x 303 D
Subwoofer Size with feet (inch)	10.25 H x 9.1 W x 11.9 D

Soundbar Weight (kg)	4.65
Soundbar Weight (pounds)	10.25

Subwoofer Weight (kg)	4.69
Subwoofer Weight (pounds)	10.35

Shipping Specifications

Unit Size (mm)	970 L x 315 W x 492.76 H
Unit Size (inch)	38.19 L x 12.4 W x 19.4 H
Unit Weight (kg)	12.7
Unit Weight (pounds)	28

Languages Supported

English, Spanish, French
Portuguese, German, Italian

Legrand reserves the right to change specifications without notice.

designed to be better™



Legrand, North America

3015 Kustom Drive
Hebron, KY 41048
United States
844.334.8044
www.legrand.us/nuvo