

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

Pulling Rope : 3/4 IN (19.100 MM) Double-Braided Composite, Rated At 26000 LB (115.600 KN). Drive Motor : 120 VAC, 50/60 Hz, 12 amps. No Load Main Capstan Speed : High Speed 28 ft/min (8.53 m/min), Low Speed 11 ft/min (3.36 m/min). No Load Secondary Capstan Speed : High Speed 68 ft/min (20.74 m/min), Low Speed 35 ft/min (10.68 m/min)

PRODUCT NAME –

Page Title

G6 TURBO™ 6000 LB Cable Puller with Floor Mount

PRODUCT OVERVIEW –

Marketing Text 1

Pulling Rope : 3/4 IN (19.100 MM) Double-Braided Composite, Rated At 26000 LB (115.600 KN)

Marketing Text 2

Drive Motor : 120 VAC, 50/60 Hz, 12 amps

Marketing Text 3

No Load Main Capstan Speed : High Speed 28 ft/min (8.53 m/min), Low Speed 11 ft/min (3.36 m/min)

Marketing Text 4

No Load Secondary Capstan Speed : High Speed 68 ft/min (20.74 m/min), Low Speed 35 ft/min (10.68 m/min)

Marketing Text 5

Pulling Force : 4000.000 LB (17.800 KN) Continuous, 5000.000 LB (22.200 KN) Intermittent, 6000.000 LB (26.700 KN) Momentary

Marketing Text 6

Floor Mount setup

Marketing Text 7

Includes : Force Gauge and foot switch

PRODUCT SPECIFICATION –

Product Specification 1

Type : Cable Puller

Product Specification 2

Application : Pulling Cable

Product Specification 3

Voltage Rating : 120 Volts AC at 50/60 Hz

Product Specification 4

Amperage Rating : 20 Amps

Product Specification 5

Mounting : Floor Mount