

THERMOSTATIC MIXING VALVE

1-844-SPEAKMAN



Prevent Scalding by using Speakman's new Point of Use Thermostatic Mixing Valve. The valve provides safe tempered water to faucets and sinks. The **ASSE 1070 TMV** ensures safe water temperatures, even if the handle rotation stop is not initially set or later re-adjusted after maintenance. In addition, our valve is the smallest ASSE 1070 TMV in the market place, making it a great option for tight spaces.

THERMOSTATIC VALVE, A-TMV

- Smallest footprint 1070 thermostatic mixing valve in the market
- 3/8" Compression male threaded connections
- Low lead brass valve body
- ASSE 1070 certified
- NSF 372, NSF 61 certified low lead
- 2.65 GPM flow rate at 45 PSI
- Minimum flow rate of 0.35 GPM
- Includes mounting bracket & hardware
- Adjustable temperature limit stop allows installer to set desired temperature
- Tamper resistant cap provides vandal resistance & inadvertent adjustments

FLOW CAPACITY OF A-TMV

PRESSURE DROP,	psi (bar)	5	10	15	20	30	40	45	50
		(0.4)	(0.7)	(1.0)	(1.4)	(2.1)	(2.8)	(3.1)	(3.4)
TEMPERED FLOW,	GPM (L/min)	0.66 (2.5)	1.2 (4.5)	1.5 (5.7)	1.74 (6.6)	2.16 (8.2)	2.51 (9.5)	2.66 (10.1)	2.8 (10.6)



THERMOSTATIC MIXING VALVE BENEFITS

- ASSE 1070 Certification ensures mixing valves are designed for use with fixtures such as sinks, lavatories or bathtubs.
- Shutoff prevents water temperatures in excess of 100°F from being delivered.
- Lead free brass construction provides unrivaled durability and complies with NSF 372 water quality requirements for plumbing fixtures.
- Adjustable temperature control allows you to set the valve at an optimal temperature range for the application.
- Tamper resistant cap prevents inadvertent temperature adjustments.