



A quality, acrylic copolymer floor polish formulated to provide a clear, wet-look, protective shine on your floors. Top Shape's advanced formula is perfect for resilient tile, terrazzo, unglazed ceramic, quarry tile, paver brick, natural stone, sealed wood, or concrete flooring.

## Features & Benefits

19% solids clear acrylic copolymer for enhanced appearance.

Self-leveling for easy application.

Minimum maintenance required.

## Item Number & Unit of Measure

Item Number	HIL8852207
Unit of Measure	5 gal BIB

## Specifications

Color	White
Fragrance	Non-Objectionable
Formula Type	Liquid

## Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

## Directions for Use

**Preparation: New floors:** After resilient flooring has been installed and the adhesive has cured for at least 2 weeks, scrub with a solution of Hillyard Recoat Prep or Assurance, following label directions, and a blue pad to remove factory finish. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard NutraRinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. **Scrub and recoat:** Scrub the existing floor polish with a solution of Hillyard Recoat Prep or Assurance, following label directions, and a blue pad. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. **Stripping:** Strip Top Shape or other polishes from the floor with a solution of Hillyard Arsenal Stripper, Devastator, or Power-Strip, following label directions. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour. **Application:** When using a sealer, apply a minimum of 5 coats of Top Shape at a rate of 1500-2000 ft<sup>2</sup>/gallon with a microfiber flat finish mop or Multi-Flo XP. Allow each coat to dry a minimum of 30 minutes before applying the next. When a sealer is not used, apply a minimum of 7 coats of Top Shape. **NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C). For best results, do not apply more than 3-4 coats per day. **Maintenance:** Use a cotton dust mop, treated with Hillyard Super Hil-Tone, daily to remove loose dirt and grit. Damp mop or autoscrub, as scheduled, with Hillyard Super Shine-All®, Top Clean®, or Arsenal® Heavy Duty Floor Cleaner. After the floor has been cleaned, gloss may be restored by spray buffing with Hillyard Hil-

## Top Shape® 19% Floor Finish (continued)



Glo®, according to label directions. Scrub and recoat, as scheduled, with a minimum of 2 coats of

Top Shape. **FLOOR PAD RECOMMENDATIONS:**

**Stripping:** black; **Scrub and Recoat:** blue;

**Autoscrubbing:** red. **NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is very porous, seal with Hillyard Hil-Tex+® or Seal 341® before applying Top Shape. If stains are a problem, seal with Strong Guard®. Do not pour unused finish or seal back into the original container.