

PROFESSIONAL GRADE DOUBLE-COATED POLYESTER FILM TAPE

TYPICAL APPLICATIONS

- Ideal for mounting, bonding and fastening applications on a wide variety of substrates including Low Surface Energy (LSE) plastics and coatings
- Ideal for use in non-direct UV exposure applications, such as vinyl and painted window frames, where clean removal is required
- Designed for mounting indoor window kits
- Trim, profile and extrusion mounting

ADVANTAGES AND BENEFITS

- Excellent adhesion to LSE plastics and coatings
- Superior cold temperature performance
- Resists plasticizer migration
- Strong PET backing ensures tape will not break when tape is applied or removed
- Easy release glassine liner
- Converter-friendly

CONSTRUCTION

Overall Grade/Function: Professional

Backing: 1 mil polyester (PET) film

Adhesive: Solvent synthetic rubber

Liner: White glassine

COLOR(S)



Clear (CLR)



STANDARD WIDTH(S) & STANDARD LENGTH(S)

Contact your Shurtape sales representative for all available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	82 oz/in width	9 N/10 mm
Thickness (with liner)	6.1 mils	0.15 mm
Thickness (without liner)	3.7 mils	0.09 mm
Elongation	100%	100%
Service Temperature Range	32 F to 230 F	0 C to 110 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-DP-391-08/27/2014