



# **Technical Data Sheet**

3M<sup>™</sup> Scotch<sup>®</sup> Fine Line Tape 265

Product Details

ŵГ Regulatory Info/SDS

**Product Description** 

Scotch® Fine Line Tape 265 is a high-performance film backed tape designed for in-mold fine line masking where sharp, clean, gel-coat color separation lines are desired.

# **Product Features**

- Easy unwind and strong backing minimizes stretch during roll unwind.
- Polypropylene backing has superior gel coat chemical resistance compared to vinyl backings.
- Silicone-rubber adhesive has excellent adhesion to semi-permanent, high-slip mold releases compared to conventional rubber-resin adhesives.
- Silicone-rubber adhesive pulls smoothly from high slip mold releases.

Polypropylene backing is conformable yet strong enough to pull sharply, evenly and consistently through gel coatings.
Silicone-rubber adhesive can be applied to surfaces at lower temperatures compared to conventional rubber-resin

adhesives.

# **Technical Information Note**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

# **Typical Physical Properties**

Attribute Name	Test Method	Value	
Color		Green matte finish	
Adhesive Type		Silicone-rubber	
Backing		Polypropylene plastic film	
Total Tape Thickness	ASTM D3652	0.13 mm (5.1 mil)	

# **Typical Performance Characteristics**

Attribute Name	Test Method	Temperature	Value
180° Peel Adhesion	ASTM D3330	22 °C (72 °F)	2.3 N/cm (21 oz/in) 1
Elongation at Break	ASTM D3759		881 %
Tensile Strength	ASTM D3759		36.8 N/cm (21 lb/in)
Short Term Temperature			93 °C (200 °F) <sup>2</sup>
Resistance			95 C (200 F) -

<sup>1</sup> 12 in/min (300 mm/min)

<sup>2</sup> Short Term (minutes, hour)

# Handling/Application Information

#### **Application Examples**

In-mold masking for gel coat color separation in:

- Boat building: Hulls, decks and small parts
  Composites: Showers, tubs, counter tops, vanities

# **Storage and Shelf Life**

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton. To obtain best performance, use this product within 12 months from date of manufacture.

#### **Available Sizes**

Attribute Name	Value
Standard Roll Length	54.8 m (60 yd)

#### **Information**

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

**Disclaimer:** 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature, has all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

# ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M Closure and Masking Systems Division 3M Center, Building 225-3S-06 St. Paul, MN 55144-1000 800-362-3550 • 877-369-2923 (Fax) www.3M.com Scotch is a registered trademark of 3M.  $\ensuremath{\mathbb{O}}$  3M 2008 (7/08)