## Low-Voltage Underground Landscape Lighting Cable

Rated 150 Volts. Rated -20°C to 60°C. Listed for Outdoor Use (Sunlight Resistant). Suitable for Direct Burial. Stranded Copper Conductors. Black PVC Insulation/Jacket.



## **APPLICATIONS**

Southwire's Low-Voltage (Low Energy) Underground Landscape Lighting Cable is suitable for outdoor accent lighting, landscape lighting and security lighting applications not exceeding 150 Volts. This product can be installed outdoors exposed to sunlight. Low-Voltage Underground Landscape Lighting Cable is suitable for use at temperatures not exceeding minimum -20°C or maximum 60°C.

## SPECIFICATIONS

- UL 1493
- CSA
- Requirements of the NEC
- RoHS Compliant

## CONSTRUCTION

Southwire's Low-Voltage Underground Landscape Lighting Cable is manufactured with two bare annealed flexible stranded copper conductors and premium-grade PVC insulation/jacket material. The insulated conductors are duplexed in a flat construction to promote easy teardown during installation. Standard color is black. White and brown colors are available, but may be subject to minimum order quantity.





Copyright 2003, Southwire Company. All Rights Reserved.

<sup>®</sup>Southwire is a registered trademark of Southwire Company.

WEIGHTS, MEASUREMENTS AND PACKAGING					
Conductor Size (AWG)	Conductor Stranding (#/AWG)	Nominal Overal Diameter (mils)	Nominal Insulation Thickness (mils)	Weight (Ibs/1000ft)	Put-Up (Ft)
16/2	26/ 30	155 x 315	45	41	250
14/2	41/30	170 x 350	45	55	250
12/2	65/30	195 x 390	45	69	250
10/2	104/30	220 x 440	45	107	250
8/2	168/30	295 x 590	60	163	250



