

1-1/2"-2" Air Admittance Valve

Job Name _____
Location _____
Engineer _____
Contractor _____
Tag _____ PO# _____

Specifications

- Constructed of plastic
- Designed to prevent sewer gases from entering the DWV piping system
- Adapter included for solvent welding to PVC/ABS pipe
- Fits 1-1/2" to 2" pipe
- Maximum pressure of 15 psi
- 3 year limited warranty

Materials

- PVC
- ABS



Dimensions and Product Offering

Part Code	DFU	Material	Description	Packaging	IN/MS	A	B	C	D
P15006	6	PVC	AAV vents up to 6 DFU	Sleeve	120/960	3.47"	2.02"	2.22"	1.95"
P15006A	6	ABS	AAV vents up to 6 DFU	Sleeve	120/960	3.47"	2.02"	2.22"	1.95"
P15020	20	PVC	AAV vents up to 20 Branch DFU and 8 Stack DFU	Sleeve	120/960	3.47"	2.02"	2.22"	1.95"
P15020A	20	ABS	AAV vents up to 20 Branch DFU and 8 Stack DFU	Sleeve	120/960	3.47"	2.02"	2.22"	1.95"

MAX DFUs

Drain Branch/Stack Size	Max DFUs on Branch	Max DFUs on Stack
1-1/2"	3	6
2"	6	24
3"	20	72
4"	160	500

Certifications/Listings/Approvals

- NSF/ANSI 14
- ASSE 1050/1051
- Conforms to IPC 2021 918.1
- Conforms to IRC P3114.1
- Conforms to UPC 2021 301.3
- Adapters conform to ASTM D2661/D2665

