


Hangs Tuff™


DWV Pipe Hanger

Patent # 5,385,320


- Strong and rigid I-beam design keeps pipe secure
- Two ring-shank nails conveniently supplied
- 100% corrosion proof, impact resistant ABS
- Can be glued to ABS or PVC pipe with all-purpose glue




Two nails supplied for easy installation.



Opposing holes are 1/2" on center.




Cradles pipe before final installation.



Locking finger holds pipe in place.



Locking finger allows installation at all angles.



Extend length by using all thread rod and vinyl-coated clamps or L-bracket.



553-8



553-9W

521-210

SUPPLY

DRAINAGE

SUPPORT

APPENDIX




Related Products

Vinyl-Coated Clamp

p 434

Item No.	Description	Dimension		Pkg	Min Qty	Case Qty
		A	B			
WHITE						
553-6W	1½" Sch. 40	8 ⁵ / ₈ "	10"	C*	50	50
553-6WPK3	1½" Sch. 40, 10/bag	8 ⁵ / ₈ "	10"	C*	1	5
553-7W	2" Sch. 40	8 ¹⁵ / ₁₆ "	10½"	C*	50	50
553-7WPK3	2" Sch. 40, 10/bag	8 ¹⁵ / ₁₆ "	10½"	C*	1	5
553-8W	3" Sch. 40	9 ⁷ / ₁₆ "	11¾"	C*	50	50
553-8WPK3	3" Sch. 40, 10/bag	9 ⁷ / ₁₆ "	11¾"	C*	1	5
553-830W	3" Sch. 30	9 ⁵ / ₁₆ "	11¾"	C*	50	50
553-830WPK3	3" Sch. 30, 10/bag	9 ⁵ / ₁₆ "	11¾"	C*	1	5
553-9W	4" Sch. 40	9 ¹⁵ / ₁₆ "	12¾"	C*	25	25
553-9WPK3	4" Sch. 40, 10/bag	9 ¹⁵ / ₁₆ "	12¾"	C*	1	5
BLACK						
553-6	1½" Sch. 40	8 ⁵ / ₈ "	10"	C*	50	50
553-6PK3	1½" Sch. 40, 10/bag	8 ⁵ / ₈ "	10"	C*	1	5
553-7	2" Sch. 40	8 ¹⁵ / ₁₆ "	10½"	C*	50	50
553-7PK3	2" Sch. 40, 10/bag	8 ¹⁵ / ₁₆ "	10½"	C*	1	5
553-8	3" Sch. 40	9 ⁷ / ₁₆ "	11¾"	C*	50	50
553-8PK3	3" Sch. 40, 10/bag	9 ⁷ / ₁₆ "	11¾"	C*	1	5
553-9	4" Sch. 40	9 ¹⁵ / ₁₆ "	12¾"	C*	25	25
553-9PK3	4" Sch. 40, 10/bag	9 ¹⁵ / ₁₆ "	12¾"	C*	1	5
L-BRACKET						
521-210	L-bracket for ¾" all thread rod			B	25	100

According to all national codes, ABS or PVC DWV pipe is to be supported every four feet or less. When hanging steel or cast iron pipe, install Hangs Tuff™ two feet on center (or less), cinch with cable tie, and anchor with min 1½", #10 wood screws.



Except 553-830W