

SAFETY DATA SHEET

1. Identification

Product identifier Universal 2-Cycle Oil - 32 fl oz

Other means of identification

Product Code No. SL2262 (Item# 1007790)

Recommended use 2-Cycle engine oil **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical Assistance** 800-521-3168 800-272-4620 **Customer Service** 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Not classified. **Health hazards**

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard Not classified. **OSHA** defined hazards

Label elements

Hazard symbol None. Signal word Warning

Combustible liquid. **Hazard statement**

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only outdoors or in a Prevention

well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply

during use and while product is drying. Wear protective gloves/protective clothing/eye

protection/face protection.

In case of fire: Do not use water jet as an extinguisher, as this will spread the fire. Response

Store in a well-ventilated place. Keep cool. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum),		64741-96-4	40 - 60
solvent-refined heavy napht	henic		

Material name: Universal 2-Cycle Oil - 32 fl oz

Chemical name	Common name and synonyms	CAS number	%
residual oils (petroleum), solvent-dewaxed		64742-62-7	20 - 40
stoddard solvent		8052-41-3	10 - 20
mineral oil		Mixture	1 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Call a physician if symptoms develop or persist. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If inhalation of a large amount does occur, call a physician immediately. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Remove and isolate contaminated clothing and shoes. Wash off with plenty of water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

If ingestion of a large amount does occur, call a poison control center immediately. Rinse mouth. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation. Prolonged or repeated skin contact may cause irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed. Runoff to sewer may create fire or explosion hazard.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

Immediately evacuate personnel to safe areas. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch or walk through spilled material. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use non-sparking tools and explosion-proof equipment. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Eliminate sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in cool place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S OSHA Components	Туре	Value	
mineral oil	TWA	5 mg/m3	
mineral oil US. OSHA Table Z-1 Limits for Ail		· ·	
Components	Type	Value	Form
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	
ACGIH			
Components	Туре	Value	Form
mineral oil	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit Value			_
Components	Туре	Value	Form
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.
stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
U.S NIOSH			
Components	Туре	Value	Form
mineral oil	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to Cher			
Components	Туре	Value	Form
distillates (petroleum), solvent-refined heavy	Ceiling	1800 mg/m3	

Material name: Universal 2-Cycle Oil - 32 fl oz

naphthenic (CAS 64741-96-4)

No. SL2262 (Item# 1007790) Version #: 01 Issue date: 06-30-2021

Components	Туре	Value	Form
	STEL	10 mg/m3	Mist.
stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
,	TWA	350 mg/m3	
US. California Code of Regulation	ons, Title 8, Section 5155. Airbo	rne Contaminants	

Components **Type** Value

PEL stoddard solvent (CAS 525 mg/m3

8052-41-3)

100 ppm

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).

Other Wear suitable protective clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Liquid. **Form** Color Blue.

Odor Mild petroleum. **Odor threshold** Not available. Not available.

-94 °F (-70 °C) estimated Melting point/freezing point 302 °F (150 °C) estimated Initial boiling point and boiling

range

Flash point

150.0 °F (65.6 °C) Cleveland Open Cup

Evaporation rate Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

0.9 % estimated

Flammability limit - upper

6 % estimated

(%)

2 hPa estimated Vapor pressure Vapor density > 1 (air = 1) Relative density 0.88 - 0.9

Solubility(ies)

Insoluble. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 449.6 °F (232 °C) estimated

Decomposition temperature Not available.

75 cSt (104 °F (40 °C)) **Viscosity**

Percent volatile Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources

of ignition.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
distillates (petroleum), solvent	t-refined heavy naphthenic	(CAS 64741-96-4)
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
mineral oil		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
Vapor		
LC50	Rat	2180 mg/kg, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
stoddard solvent (CAS 8052-4	41-3)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 3000 mg/kg

Material name: Universal 2-Cycle Oil - 32 fl oz

No. SL2262 (Item# 1007790) Version #: 01 Issue date: 06-30-2021

SDS US

Components **Species Test Results**

Inhalation

LC50 Rat > 5500 mg/m³, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

stoddard solvent (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty **Disposal instructions**

> containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Hazardous waste code Not regulated.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Material name: Universal 2-Cycle Oil - 32 fl oz

No. SL2262 (Item# 1007790) Version #: 01 Issue date: 06-30-2021

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

stoddard solvent (CAS 8052-41-3)

US. Massachusetts RTK - Substance List

distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4) stoddard solvent (CAS 8052-41-3)

US. Pennsylvania Worker and Community Right-to-Know Law

stoddard solvent (CAS 8052-41-3)

US. Rhode Island RTK

distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4) stoddard solvent (CAS 8052-41-3)

California Proposition 65



WARNING: Cancer - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

naphthalene (CAS 91-20-3) Listed: April 19, 2002

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4) residual oils (petroleum), solvent-dewaxed (CAS 64742-62-7)

stoddard solvent (CAS 8052-41-3)

No. SL2262 (Item# 1007790) Version #: 01 Issue date: 06-30-2021

Material name: Universal 2-Cycle Oil - 32 fl oz

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

Not determined

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products Not regulated

14 % VOC content (CA) 14 % VOC content (OTC)

International Inventories

New Zealand

Philippines

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

New Zealand Inventory

06-30-2021 Issue date Danica Fulmer Prepared by

Version #

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Universal 2-Cycle Oil - 32 fl oz

No. SL2262 (Item# 1007790) Version #: 01 Issue date: 06-30-2021

Nο

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).