



MANUAL BUSHING INSTALLER & REMOVAL KIT

APPLICATIONS:

General Motors 5.3L, 5.7L LS1, 6.0L LS2, 6.2L LS3 and 7.0 L engines
 Ford Coyote 5.0L, 4.6L and 5.4L Triton engines
 Other 3 and 6 spoke harmonic balancers/pulleys

BLOW MOLD CASE

To keep everything organized

FORCING SCREWS W/BEARINGS

For smoother screwing with out seizing

HEAT TREATED

For strength & durability

BLACK-OXIDE FINISH

Providing durability & rust-resistance

CONVENIENT ADAPTER

Included adapter to use bushings with shop press



Item #	Inner	Master	UPC	Packaging
W89301	0	1	039564154218	Color Box

- Allows the technician or DIY to service bushings without removing the parts reducing the possibility of damaging the bearing or suspension housings
- Saves time and frustration when servicing wheel bearings, suspension bushing, and seal replacements
- Includes 20 cups and receivers, 4 Acme thread forcing screws, 4 end

- plates, and 1 shop press adapter
- Range: External sleeve diameter 44 mm (1.73 in.) to OD 90 mm (3.54 in.)
- Acme forcing screws: M10 X 1.5, M12 X 2.0, M14 X 2.0, M16 X 2.5 mm x 450 mm (17.72 in.) long
- When access is limited or not possible, the end plates and sleeves can be used with a shop press

