

# FLS 325



## FROGTAPE® FLS 325 YELLOW LOW-STRETCH PVC FINELINE MASKING TAPE

### TYPICAL APPLICATIONS

- For demanding, high-temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry
- Also used for metal preparation, painting, coating and gel coat masking
- Used when crisp fineline edges are needed to achieve boot, cove, pin stripes or other designs

### PRODUCT FEATURES

- Waterproof and solvent-resistant
- Tough and conformable
- Crisp, fineline edge
- Can withstand high-temperature bake cycles (325 F up to 45 min)

### CONSTRUCTION

Backing: PVC Film

Adhesive: Rubber-based adhesive

### STANDARD WIDTHS

0.25 inch; 0.50 inch  
6 mm; 12 mm

### STANDARD LENGTH

36 yds  
33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	22 oz/in width	2.41 N/10 mm
Elongation	190%	190%
Service Temperature Range	40 F to 325 F (up to 45 minutes)	4 C to 163 C (up to 45 minutes)
Tensile	17 lbs/in width	29.8 N/10mm
Thickness	5.5 mils	0.14 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

