

# Quarter-Turn Dual Outlet Supply Stop Valves

|            |                 |
|------------|-----------------|
| Job Name   | _____           |
| Location   | _____           |
| Engineer   | _____           |
| Contractor | _____           |
| Tag        | _____ PO# _____ |

### Specifications

- Chrome plated finish
- Working Pressure 100 psi
- Working Temperature 40°F - 160°F

### Applications

- Hot & Cold Water Lines

### Materials

- C46500 Brass



### Dimensions and Product Offering

| Part Code     | Connections                 | A     | B     | C     | D            | E     | F     |
|---------------|-----------------------------|-------|-------|-------|--------------|-------|-------|
| <b>S10333</b> | 5/8" OD x 3/8" OD x 3/8" OD | 0.63" | 0.38" | 0.38" | 0.94" ±0.02" | 2.28" | 2.17" |
| <b>S10334</b> | 5/8" OD x 3/8" OD x 1/4" OD | 0.63" | 0.38" | 0.26" | 0.94" ±0.02" | 2.28" | 2.20" |

### Certifications/Listings/Approvals

- NSF/ANSI 14 certified
- NSF/ANSI/CAN 61 certified
- NSF/ANSI/CAN 372 certified
- ASME A112.18.1/CSA B125.1
- SDWA compliant
- IAMPO listed
- Vermont Act 193 Compliant
- Lead Law Compliant

