



**Southwire™**

# METAL BARB CABLE TIES

CABLE TIES WITH A STAINLESS STEEL BARB FOR SUPERIOR WIRE MANAGEMENT

## FEATURES

- Stainless Steel Barb provides a secure and reliable self-locking mechanism
- Safely and easily secures wire bundles and harness components
- cULus Listed per UL Standard 62275, Type 21 or 21S
- Suitable for Air Handling Spaces (AH-2)
- Available in lengths from 4" to 30" with tensile strength from 18lbs to 120lbs



**STRONG, DURABLE 304 STAINLESS STEEL BARB CONSTRUCTION FOR ENHANCED DURABILITY AND STRENGTH**

**INFINITE ADJUSTABILITY ALONG BUNDLE RANGE WITH SECURE SELF-LOCKING MECHANISM**

**MANUFACTURED USING POLYAMIDE 6.6 SUITABLE FOR INDOORS (NATURAL) AND OUTDOORS (UV RESISTANT BLACK)**

**OPERATING TEMPERATURE MINIMUM -40°F TO MAXIMUM 185°F**



**BUILT FOR DURABILITY.  
BUILT FOR RELIABILITY.  
BUILT FOR WORK.™**

**1-855-798-6657 | SOUTHWIRE.COM**

©2023 Southwire Company, LLC. All rights reserved.  
\*Registered Trademark & ™Trademark of Southwire Company, LLC.



# Southwire™

## METAL BARB CABLE TIES

PART #	TENSILE STRENGTH (LBS.)	COLOR	LENGTH	MAX. BUNDLE DIAMETER	BAG QTY.	CASE QTY.
BR4MMP0-C	18	UV BLACK	4.0"	0.8"	100	1,000
BR4MMP9-C	18	NATURAL	4.0"	0.8"	100	1,000
BR6MMP0-C	18	UV BLACK	6.3"	1.56"	100	1,000
BR6MMP9-C	18	NATURAL	6.3"	1.56"	100	1,000
BR8MMP0-C	18	UV BLACK	8.0"	2.06"	100	1,000
BR8MMP9-C	18	NATURAL	8.0"	2.06"	100	1,000
BR5IMP0-C	40	UV BLACK	5.5"	1.30"	100	1,000
BR5IMP9-C	40	NATURAL	5.5"	1.30"	100	1,000
BR8IMP0-C	40	UV BLACK	8.0"	2.06"	100	1,000
BR8IMP9-C	40	NATURAL	8.0"	2.06"	100	1,000
BR12IMP0-C	40	UV BLACK	11.8"	3.30"	100	1,000
BR12IMP9-C	40	NATURAL	11.8"	3.30"	100	1,000
BR15IMP0-C	40	UV BLACK	14.5"	4.17"	100	1,000
BR15IMP9-C	40	NATURAL	14.5"	4.17"	100	1,000
BR8SMP0-C	50	UV BLACK	8.0"	1.94"	100	1,000
BR8SMP9-C	50	NATURAL	8.0"	1.94"	100	1,000
BR12SMP0-C	50	UV BLACK	11.8"	3.18"	100	1,000
BR12SMP9-C	50	NATURAL	11.8"	3.18"	100	1,000
BR15SMP0-C	50	UV BLACK	14.5"	4.07"	100	1,000
BR15SMP9-C	50	NATURAL	14.5"	4.07"	100	1,000
BR8LMP0-L	120	UV BLACK	8.6"	2.25"	50	500
BR8LMP9-L	120	NATURAL	8.6"	2.25"	50	500
BR12LMP0-L	120	UV BLACK	11.8"	3.25"	50	500
BR12LMP9-L	120	NATURAL	11.8"	3.25"	50	500
BR14LMP0-L	120	UV BLACK	14.5"	4.07"	50	500
BR14LMP9-L	120	NATURAL	14.5"	4.07"	50	500
BR18LMP0-L	120	UV BLACK	18.0"	5.13"	50	500
BR18LMP9-L	120	UV BLACK	18.0"	5.13"	50	500
BR24LMP0-L	120	UV BLACK	24.4"	7.14"	50	500
BR24LMP9-L	120	NATURAL	24.4"	7.14"	50	500
BR30LMP0-L	120	UV BLACK	30.0"	3.31"	50	500
BR30LMP9-L	120	NATURAL	30.0"	3.31"	50	500

**BUILT FOR DURABILITY.  
BUILT FOR RELIABILITY.  
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.  
\*Registered Trademark & ™Trademark of Southwire Company, LLC.