


# UNO S™

## Concentrated Cleaner and Degreaser

UNO S™ is an aqueous based high strength degreaser which uses advanced cleaning technology to deliver outstanding performance. The excellent dissolving property of UNO S™ allows the product to achieve optimal results at ambient temperature. The foaming action of UNO S™ makes this product ideal for increased contact time and manual cleaning applications.

### Features & Benefits:

- High strength concentrate, economical to use
- Can be diluted up to 1:50 to suit all cleaning needs
- Removes oil, grease, grime, carbon deposits, markers, smoke residue, organic contaminants, dust, etc.
- Achieves optimal results at ambient temperature
- For manual use (trigger sprayer)
- Built in corrosion inhibitors to prevent flash rusting
- Water-based, non-flammable, VOC free
- Solvent, phosphate and butyl-free
- **UNO S™** is a foaming formulation
- Also available in a foamless formulation (**UNO S F™**)



Description	Size		Order No.	(M)SDS
	Metric	Imperial		
Trigger sprayer	500ml	16.9 fl. oz.	53-G 033	L-143E
Liquid	3.78L	1 gal.	53-G 036	L-143E
Liquid	20L	5.2 gal.	53-G 037	L-143E
Liquid	208L	55 gal.	53-G 038	L-143E
Liquid	1000L	264 gal.	53-G 039	L-143E

### ACCESSORIES

Spout for 5L pail	53-L 113
Spout for 20L pail	53-L 207
Faucet for 208L drum, 2"	53-L 209
Faucet for 208L drum, ¾"	53-L 210
Replacement trigger sprayer 500 ml	53-L 335

### Technical Information

Density	1.04 g/ml ( at 20°C)
Flashpoint	N/A
Odor/color	Mild odor/ light pink
pH (at 100g/L H <sub>2</sub> O)	12.5
Rinsability	Excellent
VOC	0% wt

(M)SDS available upon request or visit our web site at [www.walter.com](http://www.walter.com)

Not for product specification. The technical data contained herein is intended as reference only and may change without notice

# UNO S™

## Concentrated Cleaner and Degreaser

### Application Chart:

Equipment	Dilution ratio	Dilution %	Application	Material
Trigger sprayers	1:50 - 1:30	2,0% - 3,3%	Removal of light organic contaminants	Aluminum, Non-Ferrous Alloys, Zinc Coatings, Plastics
Trigger sprayers	1:50 - 1:10	2,0% - 10%	Removal of light organic contaminants	Steel, Stainless Steel, Plastic
Trigger sprayers	1:10 - Pure	10% - Pure	Removal of heavy organic contaminants	Steel, Stainless Steel

Dilution Chart			
Dilution ratio	Dilution %	ml of cleaner/ 1L of water	fl. oz. of cleaner/ 1 gal of water
1:50	2	20 ml	0, 68 fl. Oz.
1:40	2,5%	25ml	3,2 fl. Oz.
1:30	3,3%	33ml	4,3 fl. Oz.
1:20	5%	50ml	6,4 fl. Oz.
1:10	10%	100ml	12,8 fl. oz.
1:5	20%	200ml	25,6 fl. oz.
1:2	50%	500ml	64 fl. oz.

(M)SDS available upon request or visit our web site at [www.walter.com](http://www.walter.com)

Not for product specification. The technical data contained herein is intended as reference only and may change without notice

Walter Surface Technologies Inc.

5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1  
Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825