One Plus® Floor Finish HIL0052707





Green Seal certified. A new-generation floor polish that's formulated to be durable, easy to use, and deliver a deep gloss. One Plus will give your floors a tough and durable shine that will stand up to scuffing, scratching, and black heel marks...even in critical high traffic areas. One Plus contains no heavy metals (a potential issue for sewage treatments facilities). One Plus is a natural choice for maintaining both resilient and hard surface floors in schools, offices, hospitals, malls...and a multitude of other facilities.

Features & Benefits

Durable, easy to use, and delivers a deep gloss

Contains no heavy metals

Can apply multiple coats in one day to save time and labor

Item Number & Unit of Measure

Item Number	HIL0052707
Unit of Measure	5 gal BIB

Specifications

Color	White
Appearance	Milky Emulsion
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	RTU
PH	7.00 - 8.00
Non-Volatile Matter	18.0%

Solids Content	18.0%
Coverage SqFt/Gallon	1500-2000
Dry Time (hrs.)	1
Sheen	Gloss
Green Seal Certified	Yes
UL Certified	Yes

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

PREPARATION: Strip other polishes from the floor with HILLYARD GREEN SELECT STRIPPER, SUPER STRIP or DEVASTATOR. (Do not use abrasive pads on tile containing asbestos.) Remove the stripping solution with a wet vac. Rinse with HILLYARD NUTRA- RINSE solution and pick up with a wet vac or autoscrubber. Damp mop twice. Allow floor to dry. APPLICATION: Using a clean synthetic mop, apply 3 coats of ONE PLUS allowing a minimum of 30 minutes between coats. Additional coats of ONE PLUS may be applied, provided adequate dry time (at least one hour) is allowed between coats. Temperature, humidity, and air movement affect curing time. **NOTICE:** ONE PLUS can be used as its own seal even on porous floors. Proper drying between coats prevents pulling or streaking with any polish. For best results, allow 30 minutes drying time between coats. NOTE: Do not pour unused polish back into container. Best results are obtained with adequate ventilation and floor temperatures above 60°F (16°C).

Certifications

This product meets Green Seal Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.