

2024 Specification Sheet - English



LONG DESCRIPTION –

Long Description Marketing Copy

Cuts hard-to-reach branches from aerial basket or from the ground. Super Spool selector control for use on Open and Closed-Center hydraulic systems. Available in three lengths. Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269

PRODUCT NAME –

Page Title

Foam Filled Long Reach Chain Saw

PRODUCT OVERVIEW –

Marketing Text 1

Cuts hard-to-reach branches from aerial basket or from the ground

Marketing Text 2

Super Spool selector control for use on Open and Closed-Center hydraulic systems

Marketing Text 3

Available in three lengths

Marketing Text 4

Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269

Marketing Text 5

Safety features include: two-step trigger, trigger guard, and fully covered sprocket guard

Marketing Text 6

Anti-kickback chain and automatic chain oiler

Marketing Text 7

Rugged high torque gear motor

Marketing Text 8

Unfilled and foam-filled extension tube versions offered

PRODUCT SPECIFICATION –

Product Specification 1

Accessory : 54923 HTMA Male Coupler, 54924 HTMA Female Coupler

Product Specification 2

Application : For Use On Open And Closed-Center Hydraulic Systems

Product Specification 3

Bar Gauge : 0.058 IN (1.470 MM)

Product Specification 4

Chain Size : 0.325 IN (8.300 MM) Pitch

Product Specification 5

Cutting Capacity : 13.000 IN (330.000 MM)

Product Specification 6

Extension Type : Fiberglass - Tested To 100 KVA For 5 MINT

Product Specification 7

Flow Range : 5 - 8 GPM (19 - 30 LPM)

Product Specification 8

Length : 75.000 IN (1.600 M)

Product Specification 9

Operating Pressure : 1000 - 2000 PSI (69 - 140 BAR)

Product Specification 10

Pressure Port : 9/16-18 SAE O-Ring

Product Specification 11

Return Port : 3/4-16 SAE O-Ring

Product Specification 12

Standard : Meet OSHA Regulation 1910.269

Product Specification 13

System : Super Spool Selector Control For Use On Open And Closed-Center Hydraulic Systems

Product Specification 14

Type : Foam Filled Long Reach

Product Specification 15

Weight : 9-1/2 LB (4.400 KG)

Product Specification 16

Width : 4.000 IN (102.000 MM)