



Public

Rev:1

Effective: 06/25/99

Status: Active

Spray Lithium Lubricant

Data Sheet

3M Part No.(s)	3M Part Descriptor(s)
08875	16 oz. Aerosol

3M Fax on Demand Identification Number:

Description

3M™ Spray Lithium Lubricant is a heavy-bodied, lithium grease based, aerosol lubricant. It provides good performance under high friction loads, rubbing, and wiping action. It is excellent for general applications on all metal moving parts.

Features, Advantages, Benefits

Features	High solids lithium grease
	Non-sag
	Long lasting
	Excellent lubrication
	Handy aerosol
	Protects against rust and corrosion
	Resists heat and moisture

Advantages

Benefits

Typical Physical Properties

Container	16 oz Aerosol
Base	Lithium Grease
Color	Light Yellow
Flash Point - °F	-50°F
Consistency	Medium Paste
Solvent	Heptane
Net Weight 16 oz Can	10.5 Net Wt. Oz
Non Volatile %	35% by Weight

Product Uses

Performance Properties

Handling and Application Information

Directions for Use

1. Shake can well before using.
2. Turn spray valve so that tip points to dot on can rim.
3. Spray directly on parts to be lubricated. For hard-to-reach areas or small surfaces, use the extension tube that fits into the spray tip.
4. After use, turn can upside down and press tip until spray is free of material.

Applications

Lubrication of:

- Door hinges, trunk and hood hinges
- Cables and linkage
- Plastic to plastic sliding parts
- Metal to metal sliding parts

Storage and Handling

Store at room temperature. Rotate stock on a "first-in, first-out" basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 12 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

Country

US

This document is public. It may be distributed.

Important Notice to Purchaser

The statements and technical information contained in this technical data sheet are based on tests and data which 3M believes to be reliable, but the accuracy or completeness of such statements and technical information is not guaranteed. **3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application.

* If 'Directions for Use' reference P.N.'s 8984, 8986, or 8987, please read below.

Federal and local air quality regulations may regulate or prohibit the use of surface preparation and cleanup solvents based on VOC content. Consult your local and Federal air quality regulations for information. When using solvents, use in a well ventilated area. Extinguish all sources of ignition in the work area and observe precautionary measures for handling these materials. Refer to product label and MSDS for P.N. 8984, 8986, or 8987 for detailed precautionary information.

LIMITATION OF REMEDIES AND LIABILITY: If the 3M product is proved to be defective, **THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT.**

3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential,

regardless of the legal theory asserted, including negligence, warranty, or strict liability.

For Additional Health and Safety Information

See Material Safety Data Sheet (Fax on Demand 1-800-305-0419), or call: **3M Automotive Aftermarket Division** 3M Center, Building 223-6N-01

Phone: 877-MMM-CARS (877-666-2277)

3M Fax on Demand Identification Number

Reference: Goto Ref

Author:

Tonya L. Frisle/IM-IndMktsGp/3M/US

This is the last page