



**Materials:**

- Screws conform to SAE J429 GR 2 (exceeds ASTM A307).

**Finishes:**

- **ElectroGalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Piece (lbs)
PS6075~"x1"	1/4"	1"	EG	0.019
PS6075~"x•"	1/4"	1/2"	EG	0.014
PS6075~"x1-1/2"	1/4"	1-1/2"	EG	0.04
PS6075~"x1--"	1/4"	1-1/4"	EG	0.03
PS6075~"x€"	1/4"	3/4"	EG	0.017
PS6075~"x?"	1/4"	5/8"	EG	0.015
PS6075?"x1--"	3/8"	1-1/4"	EG	0.053
PS6075?"x1"	5/16"	1"	EG	0.026
PS6075?"x1-•"	5/16"	1-1/2"	EG	0.034
PS6075?"x1--"	5/16"	1-1/4"	EG	0.03
PS6075?"x1-€"	5/16"	1-3/4"	EG	0.04

**Project:**

**Architect / Engineer:**

**Date:**  **Phone:**

**Contractor:**

**Address:**

**Notes:**

**Approval Stamp:**