

CyberPower

CSP806UC18W HOME OFFICE SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower CSP806UC18W Surge Protector delivers reliable protection for your home or office tech. With 2400 joules of surge defense across eight AC outlets, it shields your devices—like computers, monitors, and other sensitive electronics—from power spikes caused by storms or electrical fluctuations. A sturdy six-foot cord offers flexible setup, while built-in USB-A and USB-C ports let you charge phones, tablets, and other mobile gear without tying up an outlet.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- AC Outlets: 8
- Cord Length: 6 ft
- Surge suppression: 2400 J
- Plug type: NEMA 5-15P
- Plug style: Right angle, 45° offset
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 15W
- Volts: 125 V
- Warranty: One Year Limited
- Connected Equipment Guarantee: \$300,000

SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	45° Offset Right

OUTPUT	
Outlet Type	8 x NEMA 5-15R
Outlets - Total	8
USB Charge Port Amperage COMPUTED	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 x Type A 1 x Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts



CSP806UC18W

HOME OFFICE SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6000
Surge Suppression (Joules)	2400 J
PHYSICAL	
Color	White
Form Factor	Strip
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.21 x 4.06 x 24.51 cm
Physical Dimensions - Width/Height/Depth (mm)	102 x 41 x 245 mm
Physical Dimensions - Width/Height/Depth (in.)	4.02 x 1.6 x 9.65 in.
Weight (kg)	0.63 kg
Weight (lb)	1.39 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	39.37 x 5.72 x 19.05 cm
Shipping Dimensions - Width/Height/Depth (mm)	393.7 x 57.15 x 190.5 mm
Shipping Dimensions - Width/Height/Depth (in.)	15.5 x 2.25 x 7.5 in.
Weight (kg)	0.73 kg
Weight (lb)	1.60 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	cETLus (UL1363 & UL1449 compliant) DOE VI NR Can FCC ICES-003
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty