

PRINTABLE FLATBACK PAPER TAPE

TYPICAL APPLICATIONS

- Use printed or unprinted on a variety of substrates for general purpose packaging, bundling, holding, binding, splicing, labeling, color-coding, banding, decorating and identification

ADVANTAGES AND BENEFITS

- Excellent printability
- Adhesive system designed for excellent performance and adhesion to a variety of substrates
- Flexible
- Resists abrasion, oil and staining

CONSTRUCTION

Overall Grade/Function: Printable
Backing: Flatback paper
Adhesive: Rubber-based



COLOR(S)

 White (WHI)	 Green (GRN)	 Pink (PNK)	 Fluorescent Pink (FLP)
 Black (BLK)	 Orange (ORG)	 Blue (BLU)	 Fluorescent Red (FRD)
 Red (RED)	 Yellow (YEL)	 Fluorescent Yellow (FLY)	 Fluorescent Green (FLG)

STANDARD WIDTH(S)

24 mm 48 mm (for most colors)

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	57 oz/in width	6.24 N/10 mm
Thickness	5.8 mils	0.15 mm
Elongation	2.5%	2.5%
Service Temperature Range	40 F to 150 F	4 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II, ASTM D-4236 (all except fluorescents)

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-FP-227-10/28/2014