



CRC Industries NZ, Auckland NZ

I. Product Description

Pour **CRC FiberLock®** directly into your radiator for a fast, permanent repair. **CRC FiberLock®** works on head gaskets, engine blocks, intake gaskets, cylinder heads, freeze plugs, heater cores and coolant leaks and features a powerful 3-tier formula compatible with all types of antifreeze.

Repairs leaks using three unique technologies:

Military-Strength Fibres

Proprietary lightweight fibres with a high strength-to-weight ratio make an interlocking web-like weave over the breach, ensuring a permanent, multi-layer, impenetrable repair.

Nano-Technology

A = A typical block repair product attempting to adhere to a metal surface, but the particles are too large leaving room for leaks.

B = Fiberlock® with nano-particles making a stronger more solid bond to the metal and its own particles.

Cool-X Conditioner

Cool-X Conditioner circulates in the cooling system for lower operating temperatures and improved heat transfer long after the repair is made.

II. Features & Benefits

- Permanently fixes and repairs – Head gaskets, Engine blocks, Cooling systems, Cylinder heads
- Latest technology in repair
- Nanotechnology reinforced with military-strength fibres for a superior permanent repair
- Cool-X conditioner – For lower operating temperatures and improved heat transfer
- For use in diesel or petrol cooling systems
- Easy, pour-in formula
- Value for money, quality. One bottle will repair two small cooling systems or one large system.

II. Application and Directions

Be sure to follow directions precisely as found on packaging.

CRC FiberLock® treatment ratio – Refer to owner's manual for cooling system capacity.

CRC FiberLock® works with ALL types of antifreeze and, for racing applications, can be used with straight water.

For use in the cooling system of any diesel or petrol vehicle.

For smaller cooling systems – 1/3 a bottle treats up to 10 litres.

For larger cooling systems – Use ½ bottle per 18 litres, 1 bottle will treat up to 36 litres.

IV. Typical Properties and Characteristics

Physical and Performance Characteristics:

Appearance	Beige Fibrous Liquid
Odour	Bland
Flashpoint	None
Specific Gravity	1.07
pH	11.2
Plastic Safe	Yes
Evaporation Rate	Slow



CRC Industries NZ, Auckland NZ

V. *Package Description*

Part Number	Size
1224	946ml (Bottle)

VI. *Special Precautions*

General:

Avoid contact with eyes and prolonged contact with skin.

First Aid:

If in Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

If Swallowed – Do not induce vomiting, give large quantities of water to drink.

If on Skin – Wash thoroughly.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 01/2015

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.