

SAFETY DATA SHEET

1. Identification

Product identifier Ultra-Lite 3-36® - 1 gal

Other means of identification

Product Code No. 03161 (Item# 1003429)

Recommended use Dry film lubricant Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical Assistance** 800-521-3168 800-272-4620 **Customer Service** 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Category 4 Flammable liquids Aspiration hazard Category 1 **Health hazards**

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from flames and hot surfaces. - No smoking. Use only outdoors or in a well-ventilated

> area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or

leave the area. Wear protective gloves/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. In case of fire: Do Response

not use water jet as an extinguisher, as this will spread the fire.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Material name: Ultra-Lite 3-36® - 1 gal SDS US

No. 03161 (Item# 1003429) Version #: 01 Issue date: 09-22-2021

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light		64742-47-8	80 - 90
calcium carbonate		471-34-1	0.1 - 1
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	0.1 - 1
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	0.1 - 1
distillates (petroleum), hydrotreated light naphthenic		64742-53-6	0.1 - 1
distillates (petroleum), hydrotreated light paraffinic		64742-55-8	0.1 - 1
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	0.1 - 1
distillates (petroleum), solvent-dewaxed light paraffinic		64742-56-9	0.1 - 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting. Diarrhea. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Combustible liquid. Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Type

T\//^

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

5 ma/m2

8. Exposure controls/personal protection

Occupational exposure limits

distillatos (notroloum)

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S.	· OSI	ΗA
Com	pone	nts

distillates (petroleum), hydrotreated heavy	TWA	5 mg/m3	
paraffinic (CAS 64742-54-7) US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
calcium carbonate (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	
		500 ppm	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	
		500 ppm	
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	PEL	5 mg/m3	Mist.
ACGIH			
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction

Material name: Ultra-Lite 3-36® - 1 gal

SDS US

No. 03161 (Item# 1003429) Version #: 01 Issue date: 09-22-2021

US. ACGIH Threshold Limit Values	_		_
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH			
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to Chemi			
Components	Туре	Value	Form
calcium carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
•	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy	Ceiling	1800 mg/m3	
paraffinic (CAS 64742-65-0)			

US. NIOSH: Pocket Guide to Chemical Hazards Value **Form** Components Type **TWA** 5 mg/m3 Mist. distillates (petroleum), **STEL** 10 mg/m3 Mist. solvent-dewaxed light paraffinic (CAS 64742-56-9)

Biological limit values No biological exposure limits noted for the ingredient(s).

TWA

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

5 mg/m3

Mist.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene.

Other Wear suitable protective clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

> NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. Physical state **Form** Liquid. Color Dark amber. Vanilla. Odor

Odor threshold Not available. Not available. pН

Melting point/freezing point -56.2 °F (-49 °C) estimated 432 °F (222.2 °C) estimated Initial boiling point and boiling

range

194.0 °F (90.0 °C) Setaflash Flash point

Evaporation rate Slow

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower

0.6 % estimated

Flammability limit - upper

5.5 % estimated

(%)

Vapor pressure 0.4 hPa estimated Not available. Vapor density

Relative density 0.81

Solubility(ies)

Solubility (water) Negligible. Partition coefficient Not available.

(n-octanol/water)

428 °F (220 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available.

Material name: Ultra-Lite 3-36® - 1 gal

Viscosity Not available.

Percent volatile 90.1 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactBased on available data, the classification criteria are not met. **Eye contact**Based on available data, the classification criteria are not met.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting.

Diarrhea.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Acute toxicity	May be latal if swallowed and efficies all ways.		
Components	Species	Test Results	
calcium carbonate (CAS 47	1-34-1)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 3 mg/l	
Oral			
LD50	Rat	6450 mg/kg	
distillates (petroleum), hydro	otreated heavy naphthenic (CAS 64742-5	i2-5)	
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Oral	_		
LD50	Rat	> 5000 mg/kg	
distillates (petroleum), hydro	otreated light (CAS 64742-47-8)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 5 mg/l, 4 hours	
Oral			
LD50	Rat	> 5000 mg/kg	
distillates (petroleum), hydro	otreated light naphthenic (CAS 64742-53-	-6)	
<u>Acute</u>			
Dermal			

Material name: Ultra-Lite 3-36® - 1 gal

LD50

SDS US

> 5000 mg/kg

Rabbit

Components **Species Test Results**

Inhalation

Rat LC50 2180 mg/m³, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Serious eye damage/eye

irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy paraffinic

3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-54-7)

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

No data available. Bioaccumulative potential No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty **Disposal instructions**

> containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

Material name: Ultra-Lite 3-36® - 1 gal

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

calcium carbonate (CAS 471-34-1)

US. Massachusetts RTK - Substance List

calcium carbonate (CAS 471-34-1)

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)

US. Pennsylvania Worker and Community Right-to-Know Law

calcium carbonate (CAS 471-34-1)

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)

distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)

US. Rhode Island RTK

calcium carbonate (CAS 471-34-1)

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Material name: Ultra-Lite 3-36® - 1 gal

SDS US

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

100 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

Inventory name

State

Consumer products This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50

states

 VOC content (CA)
 6.3 %

 VOC content (OTC)
 6.3 %

International Inventories

Australia

Country(s) or region

Australia	Australian inventory of industrial Chemicals (AICIS)	res
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

Australian Inventory of Industrial Chemicals (AICIS)

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date 09-22-2021
Prepared by Danica Fulmer

Version # 01

Further information CRC # 1753112

Material name: Ultra-Lite 3-36® - 1 gal sps us

On inventory (yes/no)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

Material name: Ultra-Lite 3-36® - 1 gal