

# John Guest® INCH POLYPROPYLENE FITTINGS & VALVES

FOR POTABLE WATER AND WATER TREATMENT

**SINGLE-PACKED** 



**System Benefits:**

- Quick connect and Disconnect
- Easy to use in confined spaces
- No Tools Required
- A permanent leak-proof connection
- Plastic products are lead-free and corrosion-free

**Merchandising and Distribution Benefits:**

- Strong Branding
- User Instructions on Bag
- Ziploc Bags
- English and Spanish Instructions
- Regional Sales Support

**END CAP**



PART NO.	TUBE O.D.	BAG QTY
PP4608WP	1/4"	1

**FIXED ELBOW**



PART NO.	TUBE O.D.	THREAD NPTF	BAG QTY
PP480821WP	1/4"	1/8"	1
PP480822WP	1/4"	1/4"	1
PP481222WP	3/8"	1/4"	1
PP481223WP	3/8"	3/8"	1
PP481623WP	1/2"	3/8"	1

**MALE CONNECTOR**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD x THREAD NPT		
PP010821WP	1/4" x 1/8"	1
PP010822WP	1/4" x 1/4"	1
PP010823WP	1/4" x 3/8"	1
PP010824WP	1/4" x 1/2"	1
PP011222WP	3/8" x 1/4"	1
PP011223WP	3/8" x 3/8"	1
PP011224WP	3/8" x 1/2"	1
PP011623WP	1/2" x 3/8"	1
PP011624WP	1/2" x 1/2"	1

**NPTF THREADS**

**UNION TEE**



PART NO.	TUBE OD	BAG QTY
PP0208WP	1/4"	1
PP0212WP	3/8"	1
PP0216WP	1/2"	1

**UNION ELBOW**



PART NO.	TUBE OD	BAG QTY
PP0308WP	1/4"	1
PP0312WP	3/8"	1

**UNION CONNECTOR**



PART NO.	TUBE OD	BAG QTY
PP0408WP	1/4"	1
PPM0408WP	5/16"	1
PP0412WP	3/8"	1
PP0416WP	1/2"	1

**REDUCING UNION**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD x TUBE OD		
PP201008WP	5/16" x 1/4"	1
PP201208WP	3/8" x 1/4"	1

**REDUCING TEE**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD END x TUBE OD END x TUBE OD BRANCH		
PP30121208WP	3/8"x3/8"x1/4"	1

**FAUCET CONNECTOR**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD x THREAD UNS		
PP3208U7WP	1/4" x 7/16"-24	1
PP3212U7WP	3/8" x 7/16"-24	1

7/16-24 UNS = 1/4 COMPRESSON THREADS

**FEMALE ADAPTER**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD x THREAD NPTF		
PP450822WP	1/4" x 1/4"	1
PP451222WP	3/8" x 1/4"	1

**REDUCER**



PART NO.	SIZE	BAG QTY
SIZES: STEM OD x TUBE OD		
PP061208WP	3/8" x 1/4"	1

**FEMALE CONNECTOR**



PART NO.	SIZE O.D. X UNEF	BAG QTY
PSEI6012U9P	3/8" x 9/16"-24	1

9/16 - 24 UNEF = 3/8 Compression Threads

**REDUCING UNION**



PART NO.	SIZE O.D.	BAG QTY
NC2099P	5/16" x 1/4"	1

**UNION CONNECTOR**



PART NO.	SIZE O.D.	BAG QTY
NC2112P	5/16"	1

**TUBE CUTTER**



PART NO.	SIZE	BAG QTY
TSNIP-US		1

**WATER SUPPLY KIT**



PART NO.	BAG QTY	BOX QTY
ICE MAKER KIT	1	12
WSK-W (White)	1	12
WSK-B (Blue)	1	12

Includes: 25 feet 1/4" LLDPE Tubing, (1) 1/4" Supply Valve, (1) 1/4" Connector.

**LLDPE TUBING (Smaller Coils)**



PART NO.	SIZE O.D.	COIL LENGTHS	BAG QTY	BOX QTY
PE-08-BI-025F-B	1/4"	25'	1	20
PE-08-BI-025F-N	1/4"	25'	1	20
PE-08-BI-025F-E	1/4"	25'	1	20
PEI-12-EI-025F-B	3/8"	25'	1	12
PEI-12-EI-025F-N	3/8"	25'	1	12

**STRAIGHT SHUT-OFF VALVE**



PART NO.	TUBE OD	BAG QTY
PPSV040808WP	1/4"	1
PPSV041212WP	3/8"	1

**MALE SHUT-OFF VALVE**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD x THREAD NPT		
PPSV010822WP	1/4" x 1/4"	1
PPSV011223WP	3/8" x 3/8"	1

**ELBOW SHUT-OFF VALVE**



PART NO.	SIZE	BAG QTY
SIZES: TUBE OD x THREAD NPT		
PPSV500822WP	1/4" x 1/4"	1
PPSV501222WP	3/8" x 1/4"	1

**ANGLE STOP ADAPTER VALVE**



PART NO.	SIZE	BAG QTY
SIZES: THREAD COMPRESSION x TUBE OD		
ASVPP11F	3/8" x 3/8" x 1/4"	1
ASVPP21F	3/8" x 3/8" x 3/8"	1
ASVPP51F	1/2" x 3/8" x 1/4"	1
ASVPP61F	1/2" x 3/8" x 3/8"	1

**Lead Free**

## TECHNICAL CHECKLIST FOR INCH SIZE QUICK CONNECT FITTINGS LISTED ON PAGES 13-17

### Working Pressure and Temperature Range for PP Fittings.

Water Max. 150 psi at 70°F  
 Max. 60 psi at 140°F  
 Min. 33°F/1°C

### Tube Types

**Plastic Tube** – Polyethylene, nylon and polyurethane conforming to the tolerances shown below. For soft tubing or thin wall tube we recommend the use of tube inserts.

**Braided Tube** – Use of Tube to Hose Stems listed on page 14 is essential when using braided tube or hose. The use of clamps to retain braided tube on barbs is recommended.

**Metal Tube (soft)** – Brass, copper or mild steel conforming to the tolerances below.

**Metal Tube (hard)** – We do not recommend **Super Speedfit®** fittings for hard metal or chrome plated tubes. For stainless steel and other polished metal tubes we recommend the use of Superseal fittings. These are shown on our website. It is essential that outside diameters be free from score marks and that the tube be deburred before inserting the fitting.

### Tube Tolerances

PP fittings are offered for tubes with outside diameters to the following tolerances.

Size (inches)	5/32 - 3/16	1/4 - 1/2
Tolerance (inches)	+0.001 / -0.003	+0.001 / -0.004
Size (mm)	4mm - 5mm	6mm - 22mm
Tolerance (mm)	+0.05 / -0.07	+0.05 / -0.10

### Installation and System Testing

**Fittings and tube should be kept clean and undamaged before use.**

All tube and fittings installations must be pressure tested after installation to ensure system integrity before handing over to the final user. Refer to "How to make a connection" on our website at [www.johnguest.com](http://www.johnguest.com).

### Chemicals

For use with chemicals or other potentially aggressive liquids, please contact our Technical Support Department. **Super Speedfit®** fittings are not recommended for use with explosive gases, petroleum spirits, and other fuels or for central heating systems.

### Collet Covers

Refer to our website for range of collet covers.

### Food Quality

All the fittings in this catalog are produced in Food and Drug Administration (FDA) approved



materials and are therefore recommended for food quality applications. The wetted surfaces of John Guest PP, PPSV, ASV Valves and PE Tubing are in compliance with FDA requirements for direct contact with food as detailed in 21CFR part 177.2470 for the body and 177.2600 for the O-ring. NSF International Standard 51 and 61.

### Maximum Torque Values for Plastic Threads.

Do not overtighten plastic threaded fittings as this could cause undue stress and eventual failure. Maximum recommended torque figures are shown below.

	Threads		
	1/8" - 1/4"	3/8" - 1/2"	3/4"
Maximum Torque	1.0ft lbs	2ft lbs	3ft lbs
	1.5Nm	3.0Nm	4.0Nm

It is recommended that all installations are checked prior to use to determine that a seal has been made.

The maximum torque figures quoted for use with **Speedfit®** fittings are dependent on the mating thread conforming to the relevant U.S. thread standard.

### Maintenance and Replacement Intervals

John Guest products generally require little maintenance but as a minimum we recommend routine visual inspection. Frequency of visual inspection will depend on severity of application and risk of failure. If after visual inspection John Guest products appear damaged, cracked, charred, discolored, heat distorted or corroded, they should be replaced. Any product that is or appears to be leaking should be replaced.

Product life is affected by the severity of the application, the hostility of the working environment and contact with aggressive chemicals or liquids. It is therefore important that specific replacement intervals be considered by specifiers/users/customers based on previous service life or when failure could result in unacceptable downtime, damage or injury risk.

### Cleaners and Sanitizing of Fittings

The external surfaces of John Guest products must not come into contact with oxidizing or acidic cleaners and sanitizing agents, for example (but not limited to) those below pH 4, high in sodium hypochlorite level (bleach) or containing hydrogen peroxide. Our plastic material suppliers recommend ECOLAB Oasis 133 as a suitable cleaner for the external surfaces of products manufactured by John Guest.

Several different methods exist for sanitizing the internal surfaces of fluid systems, including sodium hypochlorite, hydrogen peroxide, chlorine dioxide or ozone. It is entirely the

responsibility of the end user to determine if the chosen method is suitable for use with John Guest products over the planned working life of the system. However, to avoid unnecessary early failure, John Guest requires that the disinfection solution must be immediately flushed out at all draw off points with fresh, wholesome water at the end of the disinfection period. The solution must not be left in the system. Disinfection solutions must only come into contact with the internal (fluid carrying) surfaces of the system. If any other surfaces of a fitting come into contact with disinfection solution the whole fitting must be replaced immediately. Polypropylene fittings offer greater resistance to aggressive chemicals but does not have the same mechanical properties as other materials. John Guest polypropylene fittings are generally designated by the part number prefix PP or PPM.

### Responsibility of Use

While we give a warranty against defects in manufacture or materials, it is the responsibility of the user/installer to ensure that fittings and related products are suitable for their application. The installation must be carried out correctly in accordance with our recommendations, complying with recognized codes of practice and relevant national standards, and be properly maintained. Please refer to our terms and conditions of sale.

### Side Load

Fittings should not be subject to excessive side loads and they should not be used as support brackets. Tubing and fittings should be adequately supported to prevent excessive side loading.

### Product Selection and Installation

John Guest fittings and related products are specifically designed and manufactured by John Guest to the Technical specifications set out in the John Guest Product Catalog. All John Guest fittings and related products should be selected, installed, used and maintained in accordance with these Technical specifications. It is the customer's/user's responsibility to ensure that John Guest fittings and related products are suitable for their intended applications, and are properly installed and maintained and are used in accordance with the Technical specifications. It is also the customer's/user's responsibility to provide its customers with any relevant technical information about John Guest products it supplies them.

The company has a policy of continuous research and development and reserves the right to amend without notice the specification and design of all products illustrated in this catalog. John Guest reserves the right to change the color and shape of products. Photographs are for illustration purposes only.

Subject to our Terms and Conditions of Sale.

*John Guest USA, Inc. is not responsible for misprints or typographical errors.*