



Technical Data Sheet

3M™ Scotch® Filament Tape 8919MSR



[Product Details](#)



[Regulatory Info/SDS](#)

Product Description

Scotch® Filament Tape 8919MSR is a high-performance transparent filament tape reinforced along its length with continuous fiberglass-yarn filaments, which gives the tape a very high tensile strength. The tape is designed to hold a variety of metal appliance parts together during manufacture and shipping. The heavy clear polyester film backing provides greater stiffness and excellent abrasion, moisture, and scuff resistance. The pressure sensitive modified synthetic rubber resin adhesive is specifically formulated to provide high adhesion to oily metal surfaces, clean removal, and stain resistance on a wide variety of surfaces.

Product Features

- Balanced adhesive.
 - Good oily metal adhesion.
 - Glass filament reinforcement.
 - Less flexible tape.
 - Abrasion- and moisture-resistant.
 - Printable by the Print-Seal process.
 - High shear strength. Good initial adhesion. Generally stain resistant.
 - Minimum odor.
 - Stain resistant to most synthetic enamel and lacquer finishes.*
 - Nearly complete contact with application surface.
 - High tensile strength and impact resistance coupled with low stretch under stress.
 - Easy to dispense and handle when used with 3M dispensers.
 - Excellent protection of filaments and adhesive to allow use of less tape.
 - Provides advertising and warning capability when printed.
 - Good holding under stress with a minimum amount of tape and application effort, yet allows easy removal without excessive adhesive residue, or stayd Allows tape to be used on or in appliances during storage and shipping.
 - Doors and other movable parts are held securely in place to guard against damage.
- *Tests should be conducted when staining is a factor.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Adhesive Type		Pressure sensitive modified synthetic rubber resin
Backing		Polyester(PET)
Backing Color		Transparent
Fiber Reinforcement		Glass Yarn
Total Tape Thickness	ASTM D3652	0.18 mm (7 mil)

Typical Performance Characteristics

Attribute Name	Test Method	Dwell Time	Temperature	Substrate	Value
180° Peel Adhesion	ASTM D3330	72 h	22 °C (72 °F)	Stainless Steel	108 N/100mm (99 oz/in) ¹
Elongation at Break	ASTM D3759				5 %

Attribute Name	Test Method	Dwell Time	Temperature	Substrate	Value
Tensile Strength	ASTM D3759				6655 N/100mm (665 N/cm) (380 lb/in)

¹ 12 in/min (300 mm/min)

Handling/Application Information

Application Techniques

An extensive line of application equipment including hand-held manual dispensers, stationary definite-length dispensers, and an automatic L-Clip applicator is available. Application of Scotch® Filament Tape 8919MSR is most easily accomplished at room temperature. At lower temperatures, approaching 32°F (0°C), the adhesive becomes firm. Once applied, Scotch® Tape 8919MSR performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

Storage and Shelf Life

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock.

To obtain best performance, use this product within 18 months from date of manufacture.

Information

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M
Industrial Adhesives and Tapes Division
3M Center, Building 225-35-06
St. Paul, MN 55144-1000
800-362-3550

Scotch is a registered trademark of 3M.
©3M 2015 (6/15)