



HT600WSU2A | PREMIER HOME THEATER SURGE PROTECTOR

Protect home theater equipment, home and office computers, and other electronics

Your home entertainment system, gaming gear and devices deserve 24/7 protection. Smartphones and tablets also need surge protection when charging. Safeguard valuable electronics against voltage spikes and serious power events such as lightning-induced surges with advanced power protection. Loaded with features like fireproof and safe-fail technology, this surge protector guarantees your home and equipment stay safe. USB charging ports and a sleek outlet mounted design make it perfect for all your home entertainment needs.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 1680 J
- Plug type: NEMA 5-15P
- Outlet type: 6 NEMA 5-15R
- USB charge ports: 2 (4.8A shared)
- EMI/RFI Filtration: Yes
- LED indicators: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$250,000



SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Input Voltage Range	100-125 VAC
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
Outlets - Widely Spaced	2
USB Charge Port	Yes
USB Charge Port Amperage	4.8 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

HT600WSU2A

PREMIER HOME THEATER SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	43 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,680 J

PHYSICAL

Color	Black
Form Factors Supported	Direct Plug
Material of Construction	Plastic

DIMENSIONS

Physical Dimensions - WxHxD (cm)	12.07 x 18.01 x 4.06 cm
Physical Dimensions - WxHxD (mm)	121 x 180 x 41 mm
Physical Dimensions - WxHxD (in.)	4.75 x 7.09 x 1.6 in.
Weight (kg)	0.45 kg
Weight (lb)	0.99 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	16.0 x 24.71 x 6.3 cm
Shipping Dimensions - WxHxD (mm)	160.02 x 247.14 x 62.99 mm
Shipping Dimensions - WxHxD (in)	6.3 x 9.73 x 2.48 in.
Shipping Weight (kg)	0.49 kg
Shipping Weight (lbs.)	1.08 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	Tamper Resistant (TR) UL498A UL1449 3rd Edition cUL DoE VI NRCan FCC ICES-003

WARRANTY

CEG Amount	\$250,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited