



# Polyurethane 275 One Coat Finish

## Low VOC Oil Modified Floor Finish

Low odor polyurethane formula delivers excellent protection and brilliant gloss with only one coat.

### Features & Benefits

- Low odor formula with a maximum VOC content of 275 g/L
- Easy to apply with excellent flow, leveling and adhesion with every use
- Superior appearance and durability with only one coat - saving labor costs
- Light in color, enhancing the natural beauty of wood floors

### Applications

- For use on wood floors. Not intended for use on stone, resilient, or rubber flooring
- Designed to work in conjunction with:
  - Prominence<sup>TM/MC</sup> Heavy Duty Floor Cleaner
  - Speedtack<sup>TM/MC</sup> Clean and Burnish Restorer





# Polyurethane 275 One Coat Finish

Low VOC Oil Modified Floor Finish

## Use instructions

- Stir well before using. Blockade area. Remove gum or tape with putty knife. Dust mop floor thoroughly.
- Screen floor with #120 grit screens in 2 directions until all gloss is removed. (250 sq. ft/side). Ensure edges and corners are also properly prepared. Use hand tool or palm sander with #150 grit paper as needed. DO NOT over abrade.
- Vacuum and tack with water or Diversey Recoat Adhesion Formula and Tacking Solution.
- Allow floor to dry 30 minutes before finish application.
- Apply 1 coat Polyurethane 275 One Coat Finish using a heavy weight T-Bar and woven applicator head. Do not puddle finish and ensure adequate ventilation during drying and curing.
- Allow finish to cure for 48 hours before opening to light traffic, and a minimum of 7 days before opening for regular use. Adequate ventilation is imperative during the drying and curing process. Colder temperatures and/or high humidity will slow dry time.

## Special Handling

- Always wear appropriate personal protective equipment.
- Used finish materials (e.g., clean-up rags, steel wool, tacking towels) and sanding dust can spontaneously ignite if improperly discarded.
- Do not store waste finish materials or sanding dust in a pile or discard into the regular trash.
- Place all waste materials into a water-filled metal container and discard according to local, state and federal regulations.

Technical data	Polyurethane 275 One Coat Finish
Certifications	None
Color/Form	Clear Amber Liquid
pH	NA
Scent	Characteristic
Shelf Life	2 years*

\* When stored in unopened container at ambient temperatures. High temperatures can accelerate aging. Store on lower shelf in warehouse.

Product	Pack size	Dilution	Product code
Polyurethane 275 One Coat Finish	1 x 5 gallon / 18.9 L Container	Ready-to-Use	101104736 

## Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at [www.diversey.com](http://www.diversey.com) or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.