

17022A

6" IC Slope Ceiling Housing

Product Description

Suitable for new construction in residential and commercial applications. Designed for slope ceiling installation for ceilings from 2/12 to 6/12 pitch. The socket pivots to allow the lamp to be aimed straight down regardless of ceiling pitch. IC rated. Suitable for direct contact with insulation.

Housing
 Aluminum construction provides greater heat dissipation.
 Washington State Energy Code approved to meet restricted airflow requirements.
 Airtight housing limits the exchange of air between ceiling plenum and heated/cooled areas.
 Integral thermal protector guards against improper lamping and misuse of insulation materials.
 Adjustable socket bracket assures proper and consistent lamp positioning.
 7 1/2" height allows use in 2" x 8" joist construction.

Plaster Frame
 Housing is secured to plaster frame with screws and can be removed for access to junction box.
 Housing adjusts from 1/2" to 1 1/2" to accommodate ceiling thickness.

Junction Box
 Listed for through branch circuit wiring and includes several 3/4" knockouts.
 Four pryouts with integral strain relief simplify Romex installation.
 Supplied with three push-in wire connectors.

Hanger Bars
 Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws. Unique hanger bar lip design helps align can to joist.
 Four double-headed captive nails provide for ease of installation.
 Bars can be repositioned 90° on plaster frame without tools.
 Bars fit onto T-bar spine for quick alignment and can be permanently secured.
 Score lines allow bars to be shortened without tools to accommodate a 12" joist span.

Ordering Information

Catalog Number	Trim Color
17022A	6" IC Slope Ceiling Housing

Project

Catalog

Type

