

UTILITY GRADE CREPE PAPER MASKING TAPE

TYPICAL APPLICATIONS

- Used on a variety of substrates for general purpose packaging, bundling, holding, splicing, tabbing and banding

ADVANTAGES AND BENEFITS

- Good adhesion on variety of substrates
- Flexible and easy to use
- Excellent quick stick
- Resists water and oil

CONSTRUCTION

Overall Grade/Function: Utility

Backing: Crepe paper

Adhesive: Synthetic Rubber Solventless

COLOR(S)



STANDARD WIDTH(S)

6 mm 12 mm 18 mm
24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	20 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	43 oz/in width	4.70 N/10 mm
Thickness	5 mils	0.13 mm
Elongation	8%	8%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-CP-83-08/20/2014