



PR1500RTXL2UCTAA SMART APP SINEWAVE UPS



Protect corporate and network servers, telecom installations, and Voice Over Internet Protocol (VoIP) systems.

The PR1500RTXL2UCTAA is a Smart App Sinewave rack/tower convertible UPS with line-interactive topology, surge protection, and battery backup. CyberPower's Smart App Sinewave series has sine wave output to eliminate power gaps that can be detected by sensitive equipment and cause unexpected shutdowns.

The Smart App Sinewave PR1500RTXL2UCTAA improves battery life through battery equalization technology and Automatic Voltage Regulation (AVR), which corrects minor power fluctuations without switching to battery power. The enhanced chassis design with an easy-to-access toolless front panel, captive screws for battery panel access, and color-coded rear panel make battery changes and installations simple and fast. The PR1500RTXL2UCTAA also has an innovative LCD panel that rotates 90°, tilts for a better viewing angle, and provides information on 47 different settings including UPS stats, UPS setup and control management, and testing options.

This model accepts the BP48VP2U02TAA Extended Battery Module (EBM) for expanded runtime during power outages and the RMCARD205TAA network management card for remote management and control via a standard web browser or network management system. Includes built in cloud.

With a \$400,000 connected equipment guarantee and a three-year warranty, you can trust CyberPower's commitment to the quality of the PR1500RTXL2UCTAA.

TYPICAL APPLICATIONS

- Department Servers
- Storage Devices
- VoIP Installations
- Network Devices
- Corporate Servers
- Telecom Installations

FEATURES


- Capacity: 1500 VA / 1500 W
- Topology: Line Interactive
- Waveform: Sine Wave
- Output: 100-125 VAC +/- 5%
- Runtime (half/full): 17.9 minutes / 6.5 minutes
- Plug type & cord: NEMA 5-15P, 10-ft. cord
- Outlets: 8 surge + battery backup
- Outlet types: 8 x NEMA 5-15R
- Communication: USB, Serial, SNMP, Cloud, Relay, EPO
- Management software: PowerPanel® Business
- Remote management: Yes, with optional RMCARD205TAA
- Environmental sensor: Yes, with optional RMCARD205TAA and SNEV001
- Warranty: Three-Year
- Connected Equipment Guarantee: \$400,000
- ENERGY STAR® certified: Yes

SPECIFICATIONS

GENERAL		INPUT - CONT.	
Active PFC Compatible	Yes	Cord Length	10 ft. (3.0 m)
Energy Saving	GreenPower UPS™ Bypass Technology	Input Frequency Range	47 Hz - 63 Hz
ENERGY STAR® Certified	Yes	Input Plug Type	NEMA 5-15P
UPS Topology	Line Interactive	Input Voltage	100 - 125 VAC
INPUT		Input Voltage Range	75 VAC - 155 VAC
Adjustable Voltage Range	70 - 155 VAC	Plug Style	Right Angle, 0° Offset
Circuit Breaker	15A		

PR1500RTXL2UCTAA

SMART APP SINEWAVE UPS



SPECIFICATIONS - CONT.

OUTPUT		MANAGEMENT & COMMUNICATIONS	
Automatic Voltage Regulation	Double Boost, Single Buck	Battery Mode	
On Battery Frequency	50 Hz - 60 Hz +/- 1%	Low Battery	
On Battery Voltage	100/110/120/125 VAC +/- 5%	Overload	
On Battery Waveform	Sine Wave	Overcharge	
Outlet Type	8 x NEMA 5-15 R	Overheat	
Outlets - Battery & Surge Protected	8		
Outlets - Critical Load	4		
Outlets - Total	8		
Output Power Factor	1		
Typical Transfer Time	4ms		
VA	1500 VA		
Watts	1500 W		
BATTERY			
Battery Quantity	4		
Battery Size	12 V / 9 Ah		
Battery Type	Sealed Lead-Acid		
Extended Battery Module	BP48VP2U02TAA		
Hot-Swappable	Yes		
Replacement Battery Cartridge	1 x RB1290X4J		
Runtime at Full Load	6.5 min.	Yes - with optional RMCARD205TAA	
Runtime at Half Load	17.9 min.	Yes - with built-in RJ45 ethernet connection cloud port	
Typical Recharge Time	3 Hours	PowerPanel® Business	
User-Replaceable Battery	Yes		
SURGE PROTECTION & FILTERING			
EMI/RFI Filtration	Yes		
Surge Suppression	2430 J		
PHYSICAL			
Color	Black		
Form Factor	Rack/Tower		
Material of Construction	Metal		
Rack Height	2U		

PR1500RTXL2UCTAA

SMART APP SINEWAVE UPS

SPECIFICATIONS - CONT.

DIMENSIONS

Dimensions - Width/Height/Depth (cm)	43.43 x 8.64 x 50.04 cm
Dimensions - Width/Height/Depth (mm)	434 x 86 x 500 mm
Dimensions - Width/Height/Depth (in.)	17.1 x 3.4 x 19.7 in
Weight (kg)	30.71 kg
Weight (lbs.)	67.7 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - Width/Height/Depth (cm)	56.13 x 27.43 x 61.98 cm
Shipping Dimensions - Width/Height/Depth (mm)	561.34 x 274.32 x 619.76 mm
Shipping Dimensions - Width/Height/Depth (in.)	22.1 x 10.8 x 24.4 in
Shipping Weight (kg)	37.19 kg
Shipping Weight (lbs.)	82 lbs.

ENVIRONMENTAL

AC Mode Thermal Dissipation	71.7 BTU/hr
Operating Elevation	0 - 10,000 ft (0 - 3048 m)
Operating Relative Humidity	0 - 95 % (non-condensing)
Operating Temperature	32 - 104 °F (0 - 40 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Temperature	5 - 113 °F (-15 - 45 °C)

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1778 cUL1071 FCC Class B

WARRANTY

CEG Amount	\$400,000
Connected Equipment Guarantee	Lifetime
Extended Warranty Option	WEXT5YR-U4A
Product Warranty	3-Year Limited

