

401001

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Carefully unpack the fixture, lay out all parts on a clean surface.
2. Unscrew the lock nuts (14) from the mounting screws (3). Separate the mounting strip (2) from the canopy (13).
3. Attach the mounting strip (2) to the outlet box (1) using the outlet box screws (4).
4. Use the wire connectors (8) to connect the fixture wires to the supply wires: connect white fixture wire (11) to white supply wire (9), black fixture wire (12) to black supply wire (10), and fixture ground wire (5) to supply ground wire (7). Securely tighten all connections and carefully position the wires inside the outlet box (1).
5. Place the canopy (13) onto the mounting screws (3) and secure it firmly with the lock nuts (14).
6. Adjust the color temperature switch located on the canopy (13) to your desired setting (2700K, 3000K, 4000K, 5000K, 6500K) as shown in the illustration at the bottom right.
7. Install the shade (15) by twisting it onto the canopy (13) until it is firmly secured.

8. Turn on the power and test the light fixture.

INSTALLATION IS NOW COMPLETED

