

P-670



HEAVY DUTY DUCT TAPE

TYPICAL APPLICATIONS

- For sealing and seaming ductwork in the HVAC industry
- Can also be used for protection, splicing, bundling, seaming and sealing applications that demand higher tensile strength and easy tear capabilities
- Can also be used for temporary and permanent applications in the auto industry

PRODUCT FEATURES

- High adhesion and tack
- Conformable
- Hand-tearable
- Delamination-resistant

CONSTRUCTION

Overall Grade/Function: Heavy Duty

Backing: Polyethylene coated cloth

Adhesive: Synthetic rubber

STANDARD WIDTH(S)

24 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



BLACK
(BLK)



WHITE
(WHI)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	95 oz/in width	10.40 N/10 mm
Thickness	11.5 mils	0.29 mm
Elongation	3%	3%
Service Temperature Range	50 F to 180 F	10 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

