


STAINLESS STEEL REDUCING (FACE) BUSHING

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- NPT Male by NPSM Female Threads
- No package quantity required

Applications:

Designed for use with stainless steel conduit to reduce sizes of threaded stainless conduit, nipples and other threaded fittings.



Part Number	Trade Size (in)	A (Height) (in)	B (Width) (in)	Wall Thickness (in)	Weight per each (in)
S60700FB05	¾ x ½	0.750	1.010	0.013	0.05
S61000FB05	1 x ½	0.760	1.280	0.250	0.14
S61000FB07	1 x ¾	0.760	1.290	0.013	0.07
S61200FB05	1¼ x ½	1.000	1.630	0.430	0.40
S61200FB07	1¼ x ¾	1.000	1.640	0.330	0.32
S61200FB10	1¼ x 1	1.000	1.640	0.210	0.18
S61500FB05	1¼ x ½	1.000	1.860	0.556	0.60
S61500FB07	1½ x ¾	1.000	1.870	0.445	0.50
S61500FB10	1½ x 1	1.020	1.870	0.320	0.36
S61500FB12	1½ x 1¼	1.025	1.880	0.160	0.14
S62000FB05	2 x ½	1.020	2.360	0.800	1.06
S62000FB07	2 x ¾	1.000	2.360	0.700	0.92
S62000FB10	2 x 1	1.000	2.360	0.560	0.79
S62000FB12	2 x 1¼	1.000	2.360	0.400	0.58
S62000FB15	2 x 1½	1.020	2.360	0.280	0.38

All dimensions are for informational purposes only *Tolerances +/- 5%

Note: Contact factory for 2-½" - 6"

