



General Purpose Masking Tape

2030

FOD# 1514

page 1 of 2

Technical Data

September 1, 1998

Supersedes February 1, 1997

Product Description A general purpose high adhesion masking tape for paint masking and many other jobs on the construction site.

Product Construction Backing: Natural colored crepe paper
Adhesive: Rubber
Standard Roll Length: 60 yds. (54.8m)

Typical Physical Properties **Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM TEST METHOD
Adhesion to Steel:	39 oz./in. width (43 N/100mm)	D-3330
Tensile Strength:	23 lbs./in. width (350 N/100mm)	D-3759
Elongation at Break:	8%	D-3759
Tape Thickness:	0.0056 in. (0.14mm)	D-3652

- General Information**
1. Tape 2030 should not be subjected to outdoor exposure. Tape may become very difficult to remove.
 2. Tape 2030 should be removed within 24 hours of being applied for best results.
 3. Tape 2030 has very good resistance to adhesive transfer to a surface.
 4. Tape 2030 is manufactured in an ISO 9002 registered plant to meet worldwide quality standards.

Shelf Life To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Features	FEATURES	ADVANTAGES	BENEFITS
	Rubber adhesive	Instant adhesion	Sticks easily/helps reduce labor
		Good holding power	Helps resist lifting or curling/helps reduce rework
	Crepe paper backing	Conformability	Easy handling/helps reduce time involved

Features (cont.)	FEATURES	ADVANTAGES	BENEFITS
	Backing saturant	Easy tear	Good handling/helps reduce waste
		Solvent and moisture resistance	Helps resist paint bleed-through/helps reduce rework
	Backsize treatment	Controlled unwind	Easy to use/helps reduce waste
	Manufactured without solvents	Eliminates use of organic solvents during manufacture	Helps minimize energy and raw material consumption during manufacture

Technical Information and Data

The technical information and data, recommendations, and other statements provided are based on tests or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

The 3M product will be free from defects in material and manufacture for a period of one (1) year from the date of manufacture. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. If the 3M product is defective within the warranty period stated above, your exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, warranty, negligence, or strict liability.



This Industrial Tape and Specialties Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



Industrial Tape and Specialties Division

3M Center, Building 220-7W-03
St. Paul, MN 55144-1000
USA
1 800.722.5463
1 800.223.7427 Fax On Demand
www.3M.com