

FOOD ZONE V™

High Viscosity Food Grade Lubricant

Industrial lubricant for heavy duty applications and chains lubrication in food and beverages processing environments

Features & benefits

- NSF approved H1 FOOD GRADE LUBRICANT for incidental contact with food (registration number 148374)
- Thick non drying film to extend equipment life and lubricate moving and sliding parts
- Foaming formula for maximum penetration and adherence
- PTFE additives for maximum wear and friction protection
- Plastic and rubber compatible
- Non-conductive
- Water resistant
- Resists chemical attack
- Temperature range: -35°C to 135°C (-31°F to 275°F)
- Temporary corrosion protection

DESCRIPTION	SIZE	ORDER NO.	(M)SDS
Aerosol	400 ml / 13.5 oz	53 D 652	L-154E

Remove with:

Slap Shot aerosol, 500ml 53-C 502
 Slap Shot sprayer, 500ml 53-C 503
 Slap Shot, 5L 53-C 506
 Slap Shot, 20L 53-C 507
 Slap Shot, 200L 53-C 508
 Slap Shot PL aerosol, 500ml 53-C 552

Technical information

Density (20°C/68°F)	0.79g/ml
VOC	14.5% (w/w)
Flash Point	-97°C / -142.6°F
Odor/color	Mild/whitish
Dielectric Strength	Non conductive
Solubility in water	Not miscible or difficult to mix
Viscosity	N/D
Shelf Life	2 years in closed container

(M) SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.