

42102/42106

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

- Carefully unpack the fixture, lay out all parts on a clean surface.
- Securing the rods, screw rod (18") onto bushing A (2). Screw rod (12") into bushing B (4). Screw rod (6") into bushing C (6). Expending on desired height to chose Rod 6",12",18" then securing loop onto the rod.
- Adjust the length of the chain (7), if necessary, use pliers (not included) to spread links of chain (7) apart and remove any links to achieve desired hanging height. Connect the chain to the fixture loop (9) and loop (11) on the canopy by K/D ring (8).
- Mount the mounting bracket (12) to the outlet box (13) by using two outlet box screws (15). Make sure the threads of the mounting screws (14) are facing out when the mounting bracket (12) is attached to the outlet box (13).
- Tie the ground wires (18&26)** from fixture and from outlet box to the ground screw (17) on the mounting bracket (12). Connect the wire with writing (20) from the fixture to the white wire (neutral wire 23) from the supply circuit. Connect the wire without writing (22) from the fixture to the black wire (live wire 21) from the supply circuit.
- Cover the connections by using provided wire connectors (18). Position wires back inside the outlet box.
- Place the canopy (10) over the outlet box (11). Align the mounting screws (24) so that they protrude through the appropriate holes on the canopy (10). Screw the lock nuts (20) onto the mounting screws (24).
- Install the bulb (25 not included) into the socket. Make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label.
- Turn on the power

INSTALLATION IS NOW COMPLETED

