according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SeamGrip
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation Adhesives
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

McNett Corporation

1411 Meador Avenue

Bellingham, WA 98229-5845

Phone: 360-392-2732

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335+H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20-40-48/20-63: Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of

serious damage to health by prolonged exposure through inhalation. Possible risk of

harm to the unborn child.

(Contd. on page 2)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 1)

Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

🀞 F; Highly flammable

R11: Highly flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

4,4'-methylenediphenyl diisocyanate

toluene

· Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.

H335+H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Contains isocyanates. May produce an allergic reaction.

Contains 4,4'-methylenediphenyl diisocyanate. May produce an allergic reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

(Contd. on page 3)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P285 In case of inadequate ventilation wear respiratory protection. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P285 In case of inadequate ventilation wear respiratory protection. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray. P285 In case of inadequate ventilation wear respiratory protection. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P285 In case of inadequate ventilation wear respiratory protection. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P281 Use personal protective equipment as required. P240 Ground/bond container and receiving equipment.
P240 Ground/bond container and receiving equipment.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse
skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362 Take off contaminated clothing and wash before reuse.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for
breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P363 Wash contaminated clothing before reuse.
P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a
position comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international
regulations.

· Hazard description:

· WHMIS-symbols:

B2 - Flammable liquid

D2A - Very toxic material causing other toxic effects

(Contd. on page 4)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 3)



· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

12 Health = *2 3 Fire = 3

* - Indicates a long term health hazard from repeated or prolonged exposures.

· HMIS Long Term Health Hazard Substances

101-68-8 4,4'-methylenediphenyl diisocyanate

108-88-3 toluene

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	> 50%
EINECS: 202-966-0	Xn R20-40-48/20; Xn R42/43; Xi R36/37/38	
Index number: 615-005-00-9	L	
	Resp. Sens. 1, H334; STOT RE 2, H373	
	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
	Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 108-88-3	toluene	25-50%
EINECS: 203-625-9	xn R48/20-63-65; xi R38; F R11	
Index number: 601-021-00-3		
	Repr. Cat. 3	
	♦ Flam. Liq. 2, H225	
	& Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304	
A LEG LI C	♦ Skin Irrit. 2, H315; STOT SE 3, H336	

· Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. on page 5)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 4)

4 First aid measures

· 4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

Do not pull solidified product off the skin.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Dizziness

Headache

Coughing

Breathing difficulty

Gastric or intestinal disorders

Cyanosis

· Hazards

Danger of pulmonary oedema.

Danger of cerebral oedema.

Danger of convulsion.

Danger of impaired breathing.

Condition may deteriorate with alcohol consumption.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

Monitor circulation, possible shock treatment.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

If blue colouring appears (lips, ear-lobes, finger-nails), give oxygen treatment as quickly as possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 5)

5 Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Hydrogen cyanide (HCN)

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Danger of receptacles bursting because of high vapour pressure when heated.

5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water haze or fog.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Protect from heat.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Take note of emission threshold.

(Contd. on page 7)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 6)

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities. Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Emergency cooling must be available in case of nearby fire.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

Provide ventilation for receptacles.

· Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Store away from oxidizing agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
101-68-8 4,4'-methylenediphenyl diisocyanate		
PEL (USA)	Short-term value: C 0,2 mg/m³, C 0,02 ppm	
REL (USA)	Short-term value: C 0,2* mg/m³, C 0,02* ppm	
	Long-term value: 0,05 mg/m³, 0,005 ppm	
	*10-min	
TLV (USA)	0,051 mg/m ³ , 0,005 ppm	
EL (Canada)	Short-term value: C 0,01 ppm	
,	Long-term value: 0,005 ppm	
	Skin; S	
EV (Canada)	0,005 ppm	
,	(Contd. on page 8)	

Safety Data Sheet ording to 1907/2006/EC (REAC

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

	(Contd. of page 7)
108-88-3 tolu	iene
PEL (USA)	Short-term value: C 300; 500* ppm
	Long-term value: 200 ppm
	*10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m³, 150 ppm
	Long-term value: 375 mg/m³, 100 ppm
TLV (USA)	75 mg/m³, 20 ppm
, ,	BEI
EL (Canada)	20 ppm
, ,	R ···
EV (Canada)	

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- $\cdot \ \textbf{Personal protective equipment:}$
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Contact lenses should not be worn.

(Contd. on page 9)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 8)



Safety glasses

Goggles recommended during refilling

· Body protection: Protective work clothing

9.1 Information on basic physical and chemical properties General Information		
Form:	Viscous	
Colour: · Odour:	Clear Aromatic	
· Odour. · Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	115°C (239 °F)	
· Flash point:	20°C (68 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	520°C (968 °F)	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air, vapour mixtures are possible.	
· Explosion limits:		
Lower:	0,4 Vol %	
Upper:	7,0 Vol %	
· Vapour pressure at 20°C:	29 hPa	
· Density at 20°C:	1 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 9)

· Viscosity:

Dynamic at 20°C: 6250 mPas **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 22 % (as VOCs)

• 9.2 Other information No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: Avoid temperatures above 49 °C / 120 °F.
- · 10.3 Possibility of hazardous reactions

Temperatures above 49 °C / 120 °F may result in hazardous reactions.

Flammable.

Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.

Contact with acids releases toxic gases.

Reacts with catalysts, oxidizing agents and strong alkali.

Used empty containers may contain product gases which form explosive mixtures with air.

Corrosive action on metals.

· 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

- 10.5 Incompatible materials: Contact with acids liberates toxic gases.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Hydrogen cyanide (prussic acid)

Poisonous gases/vapours

Irritant gases/vapours

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:		
101-68-8 4	I,4'-methy	lenediphenyl diisocyanate
Oral	LD50	2200 mg/kg (mouse)
108-88-3 t	oluene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

(Contd. on page 11)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Revision: 10.09.2012 Printing date 10.09.2012

Trade name: SeamGrip

(Contd. of page 10)

- · Primary irritant effect:
- · on the skin: Slight irritant effect on skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Product is suspected to cause birth defects.

Vapours have narcotic effect.

- · Acute effects (acute toxicity, irritation and corrosivity) Danger through skin adsorption.
- **Sensitisation** Sensitization possible by inhalation and/or dermal contact.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: The product contains materials that are harmful to the environment.
- 12.2 Persistence and degradability The product is partly biodegradale. Significant residuals remain.
- · 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

This statement was deduced from the properties of the single components.

The product contains materials that are harmful to the environment.

Due to the consistence and the low watersolubility of the product a bioavailability is not probable.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

(Contd. on page 12)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 11)

Damaged materials pose a danger to anyone in the immediate area; consult experts for disposal of damaged products.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

4 Transport information	
· 14.1 UN-Number · DOT, ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name · DOT · ADR · IMDG, IATA	FLAMMABLE LIQUID, N.O.S. 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE) FLAMMABLE LIQUID, N.O.S. (TOLUENE)
· 14.3 Transport hazard class(es)	
· DOT	
PARAMETER COLUMN	
· Class	3 Flammable liquids.
· Label	3
· ADR	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · DOT, ADR, IMDG, IATA	III
14.5 Environmental hazards:Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

	(Contd. of page 12)
Danger code (Kemler):EMS Number:	33 F-E, <u>S-E</u>
· 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR · Tunnel restriction code	D/E
· UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (TOLUENE), 3, III

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- · SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Carcinogenic Categories

· EPA (Environmental Protection Agency)			
101-68-8	4,4'-methylenediphenyl diisocyanate	CBD	
108-88-3	toluene	II	

· IARC (International Agency for Research on Cancer)

101-68-8	4,4'-methylenediphenyl diisocyanate	3
108-88-3	toluene	3

(Contd. on page 14)

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Revision: 10.09.2012 Printing date 10.09.2012

Trade name: SeamGrip

	_
· TLV (Threshold Limit Value established by ACGIH))
108-88-3 toluene A4]
· NIOSH-Ca (National Institute for Occupational Safety and Health)	Ī
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	1
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.]
· Canadian Ingredient Disclosure list (limit 0.1%)]
101-68-8 4,4'-methylenediphenyl diisocyanate]
· Canadian Ingredient Disclosure list (limit 1%)	
108-88-3 toluene	
· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	_

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for

any specifi	c product features and shall not establish a legally valid contractual relationship.
Relevant p	hrases
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
R11	Highly flammable.
R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R42/43	May cause sensitisation by inhalation and skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.
	(Contd. on page 1:

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 10.09.2012 Revision: 10.09.2012

Trade name: SeamGrip

(Contd. of page 14)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent