

FROGTAPE® PREMIUM GRADE, DOUBLE-SIDED POLY-HANGING CONTAINMENT TAPE

TYPICAL APPLICATIONS

- For holding poly-sheeting and other protective materials when creating high-performance containment systems
- Use for restoration, abatement and remodeling tasks such as painting, cleaning, sanding, mold remediation, asbestos removal and more
- May be used on a variety of surfaces, including drywall, wood trim, glass, plastic and vinyl

PRODUCT FEATURES

- Double-sided containment tape offers a 50% time savings compared to standard poly-hanging methods on average and removes quickly and easily
- Two Tapes in One: (1) Side one has a premium grade painter's tape adhesive that offers 21-day clean removal; (2) Side two has an aggressive adhesive to securely hold poly-sheeting
- Excellent holding ability and can be used on a variety of surfaces, including painted walls, woodwork, glass, metal and vinyl
- Conforms well to uneven surfaces for full containment even if the surface is not smooth and can be repositioned

CONSTRUCTION

Backing: Fine structured crepe

Adhesive: Synthetic rubber adhesive

Liner: Super-calendered kraft (SCK)

STANDARD WIDTHS

1.41 in; 1.88 in

36 mm; 48 mm

STANDARD LENGTH

25 yd

22.8 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel - Exposed Side	27 oz/in width	2.96 N/10 mm
Adhesion to Stainless Steel - Liner Side	60 oz/in width	6.57 N/10 mm
Elongation	9%	9%
Service Temperature Range	32 F to 120 F	0 C to 49 C
Tensile	21 lbs/in width	36.8 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

