



MP1047SE MULTI-PACK SOLUTION

Allow more convenient placement
of electrical equipment

The Connect and Protect + USB Combo Pack offers the team of GC106U, a 1 AC Outlet + USB Combo, and P806U, Power + Protection in One. This combo pack provides versatile power and protection where you need it. Perfect for home or office environment, quickly charge multiple devices using AC power and USB charging.

The GC106U is a versatile power source that provides one AC grounded outlet for standard-sized plugs, and two USB charging ports with 2.4 shared Amps to charge USB devices fast. The GC106U also has a 6-foot braided power cord with a low-profile plug which places charging power where you need it, and it will fit tightly behind furniture.

The P806U is a surge suppressor that protects your data and electronic devices from damage caused by power spikes and surges. It has six standard-spaced grounded outlets and two wide-spaced outlets for standard-sized and wide-sized plugs. With 2 USB charging ports, it provides 2.4 shared amps to charge USB devices quickly. The P806U has safe-fail protection which cuts the power to connected equipment when the unit can no longer provide surge protection. Safe-fail protects your connected devices by alerting you that they are no longer surge protected. With a 6-foot power cord with low-profile plug, it puts charging power where you need it and will fit in tight spaces.



TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES - SURGE PROTECTOR POWER STRIP P806U

- Surge suppression: 2,700 Joules
- Volts: 125 V
- Circuit breaker: 15 A
- USB ports: 2 (2.1-Amp)
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 8 x NEMA 5-15R
- Transformer outlets: 2
- Power cord: 6 ft.
- LED Indicators: Yes
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000

FEATURES - 1-OUTLET USB CHARGING CORD GC106U

- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 1 NEMA 5-15R
- USB charge ports: 2 (2.4-Amp)
- Warranty: One-Year Limited

MP1047SE

MULTI-PACK SOLUTION

SPECIFICATIONS

	P806U POWER STRIP	GC106U CHARGING CORD	P806U POWER STRIP	GC106U CHARGING CORD
INPUT				
Circuit Breaker	15A			
Plug Type	NEMA 5-15P			
Plug Style	Right Angle, 45° Offset			
Cord Length	6 ft (1.8 m)			
Input Voltage	125 VAC			
OUTPUT				
Outlet Type	NEMA 5-15R			
Outlets - Total	8	1		
USB Charge Ports	2 USB-A			
USB-A Charge Port Output	2.4A (shared)			
USB-A Charge Port Voltage	5 VDC			
SURGE PROTECTION & FILTERING				
Attenuation	30 dB			
Surge Suppression	2,700 J	N/A		
Clamping Voltage	600V (H-N, H-G, N-G)	N/A		
Maximum Surge Current	105,000 A	N/A		
Maximum Surge Current H-G	30,000 A	N/A		
Maximum Surge Current H-N	45,000 A	N/A		
Maximum Surge Current N-G	30,000 A	N/A		
Maximum Surge Voltage	6,000 V	N/A		
Response Time	< 1 Nanosecond	N/A		
EMI/RFI Filtration	150 KHz 100 MHz Yes	N/A		
INDICATORS				
LED Indicators	Protected (green) Grounded (green)		N/A	
PHYSICAL				
Color	White			
Keyhole Mounting Slots	Yes	No		
Material of Construction	Plastic			
DIMENSIONS				
Product Dimensions (WxHxD) cm	9.91 x 3.1 x 19.81 cm	4.5 x 2.49 x 11.0 cm		
Product Dimensions (WxHxD) mm	99 x 31 x 198 mm	45 x 25 x 110 mm		
Product Dimensions (WxHxD) in	3.9 x 1.22 x 7.8 in	1.77 x 0.98 x 4.33 in		
Shipping Dimensions (WxHxD) cm	33.02 x 43.18 x 5.08 cm			
Shipping Dimensions (WxHxD) mm	330.2 x 431.8 x 50.8 mm			
Shipping Dimensions (WxHxD) in	13 x 17 x 2 in			
Shipping Weight (kg)	1.16 kg			
Shipping Weight (lbs.)	2.56 lbs			
CERTIFICATIONS				
Environmental	RoHS Compliant			
Safety	UL1363 UL1449 3rd Edition cUL	UL60950 1310 cUL FCC ICES-003 DOE VI NRCan		
WARRANTY				
CEG Amount	\$300,000	\$0		
Connected Equipment Guarantee	Lifetime	None		
Product Warranty	One-Year Limited			