

# **Safety Data Sheet**

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 27-7947-8
 Version Number:
 3.00

 Issue Date:
 05/24/18
 Supercedes Date:
 09/05/14

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> W9910 Wind Tape Adhesion Promoter Packets

#### **Product Identification Numbers**

70-0066-6803-5

### 1.2. Recommended use and restrictions on use

### Recommended use

Industrial use

### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Electrical Markets Division

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

## 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

### 2.1. Hazard classification

Flammable Solid: Category 1.

Serious Eye Damage/Irritation: Category 2A.

Specific Target Organ Toxicity (single exposure): Category 3.

## 2.2. Label elements

# Signal word

Danger

### **Symbols**

Flame | Exclamation mark |

## **Pictograms**





#### **Hazard Statements**

Flammable solid.

Causes serious eye irritation.

May cause drowsiness or dizziness.

### **Precautionary Statements**

#### **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

### Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

4% of the mixture consists of ingredients of unknown acute oral toxicity.

4% of the mixture consists of ingredients of unknown acute dermal toxicity.

4% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
NON-WOVEN PAD	None	30 - 60 Trade Secret *
ISOPROPYL ALCOHOL	67-63-0	15 - 40 Trade Secret *
PROPYL ALCOHOL	71-23-8	10 - 30 Trade Secret *
POLYAMIDE RESIN	68989-76-4	3 - 7 Trade Secret *
WATER	7732-18-5	1 - 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

**Substance** Carbon monoxide Carbon dioxide

## Condition

**During Combustion During Combustion** 

# 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as

> Page 3 of 10

possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
ISOPROPYL ALCOHOL	67-63-0	ACGIH TWA:200 ppm;STEL:400 ppm A4: No		A4: Not class. as human
				carcin
ISOPROPYL ALCOHOL	67-63-0	OSHA	TWA:980 mg/m3(400 ppm)	
PROPYL ALCOHOL	71-23-8	ACGIH	TWA:100 ppm	A4: Not class. as human
				carcin
PROPYL ALCOHOL	71-23-8	OSHA	TWA:500 mg/m3(200 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

**Indirect Vented Goggles** 

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

Select and use groves and/or protective crothing approved to relevant rocal standards to prevent skin contact based on the

**Page 4 of** 10

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer Nitrile Rubber

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**General Physical Form:**Solid (Liquid on a solid pad) **Specific Physical Form:**Liquid on a non-woven pad

Odor, Color, Grade: Clear liquid with solvent odor absorbed on a non-woven pad

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot Applicable

**Boiling Point** Approximately 181 °F [Details: For liquid portion]

Flash Point 57 °F [Test Method: Closed Cup] [Details: Based on liquid only.]

**Evaporation rate**No Data Available

Flammability (solid, gas) Flammable Solid: Category 1.

Flammable Limits(LEL) 2 % volume Flammable Limits(UEL) 12.7 % volume

**Vapor Pressure** <=33 mmHg [@ 68 °F] [Details: For liquid portion]

Vapor Density 2.1 [Ref Std: AIR=1]

**Density** 0.82 g/ml [*Details*: For liquid portion]

Specific Gravity 0.82 [@ 68 °F] [Ref Std: WATER=1] [Details: For liquid

portion]
Appreciable
No Data Available
No Data Available

**Autoignition temperature** 750 °F

Decomposition temperatureNo Data AvailableViscosity50 - 100 centipoiseAverage particle sizeNo Data AvailableBulk densityNo Data AvailableHazardous Air PollutantsNo Data AvailableMolecular weightNo Data Available

**Volatile Organic Compounds** 746 g/l [*Test Method*:calculated SCAQMD rule 443.1]

Percent volatile 94 % weight
Softening point No Data Available

VOC Less H2O & Exempt Solvents 746 g/l [Test Method:calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Solubility in Water

Solubility- non-water

Partition coefficient: n-octanol/ water

**Page 5 of** 10

05/24/18

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames Heat

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

# 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

### **Skin Contact:**

Prolonged or repeated exposure may be harmful. Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

### **Eve Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Page 6 of** 10

May cause additional health effects (see below).

### **Additional Health Effects:**

## Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value		
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg		
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l		
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg		
ISOPROPYL ALCOHOL	Dermal	Rabbit	LD50 12,870 mg/kg		
ISOPROPYL ALCOHOL	Inhalation- Vapor (4 hours)	Rat	LC50 72.6 mg/l		
ISOPROPYL ALCOHOL	Ingestion	Rat	LD50 4,710 mg/kg		
PROPYL ALCOHOL	Dermal	Rabbit	LD50 4,000 mg/kg		
PROPYL ALCOHOL	Inhalation- Vapor (4 hours)	Rat	LC50 > 34 mg/l		
PROPYL ALCOHOL	Ingestion	Rat	LD50 estimated to be 2,000 - 5,000 mg/kg		

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Skin Corrosion/irritation	Ann Corrogion, irritation					
Name	Species	Value				
ISOPROPYL ALCOHOL	Multiple animal species	No significant irritation				
PROPYL ALCOHOL	Rabbit	Minimal irritation				

Serious Eye Damage/Irritation

Name	Species	Value
ISOPROPYL ALCOHOL	Rabbit	Severe irritant
PROPYL ALCOHOL	Rabbit	Severe irritant

### **Skin Sensitization**

Name	Species	Value
ISOPROPYL ALCOHOL	Guinea	Not classified
	pig	
PROPYL ALCOHOL	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
ISOPROPYL ALCOHOL	In Vitro	Not mutagenic

3M <sup>TM</sup> W9910 Wind Tape Adhesion Promoter Packets 05/24/18	3MTM W9910	Wind Tape	Adhesion	Promoter Packets	05/24/18
---	------------	-----------	----------	------------------	----------

ISOPROPYL ALCOHOL	In vivo	Not mutagenic
PROPYL ALCOHOL	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
ISOPROPYL ALCOHOL	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification
PROPYL ALCOHOL	Ingestion	Rat	Some positive data exist, but the data are not
	_		sufficient for classification

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesi s
ISOPROPYL ALCOHOL	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
PROPYL ALCOHOL	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.6 mg/l	6 weeks
PROPYL ALCOHOL	Inhalation	Not classified for development	Rat	NOAEL 8.6 mg/l	during gestation

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ISOPROPYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ISOPROPYL ALCOHOL	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
ISOPROPYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
PROPYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Mouse	NOAEL 5 mg/l	4 hours
PROPYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	
PROPYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
ISOPROPYL ALCOHOL	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
ISOPROPYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
PROPYL ALCOHOL	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 70 mg/kg/day	83 weeks
PROPYL ALCOHOL	Ingestion	liver	Not classified	Rat	LOAEL 70 mg/kg/day	83 weeks

Page 8 of 10

05/24/18

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product—that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

#### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

### **Health Hazards**

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

#### 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **HMIS Hazard Classification**

**Health:** 2 Flammability: 3 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 27-7947-8
 Version Number:
 3.00

 Issue Date:
 05/24/18
 Supercedes Date:
 09/05/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

## 3M USA SDSs are available at www.3M.com

**Page** 10 of 10